

FR20107-2 Cavity filter, reject, high Q, one 7" cavity, 132-150 MHz

Also referred as: FR20107*2

- 7 inch diameter aluminum cylinder with brass and copper coaxial inner conductor
- Silver plating and chromate conversion coating limit corrosion and enhance performance
- Temperature compensated for extremely low frequency drift

The notch (reject) filters provide exactly the opposite response to a bandpass filter — they “notch out” or reject an unwanted frequency, while passing all others. An essentially symmetrical response is obtained where a passband is required, both above and below the notch reject frequency. In order to be easily field-tuned, a rotatable loop permits variable notch depth and a fine tuning nut allows for fine frequency adjustment.

The FR series notch filters are designed to:

- Suppress sideband noise from multicoupled transmitters on one co-located receiver frequency.
- Protect multicoupled receivers further from front-end overload by the carrier of one co-located transmitter.
- Generally, “Protect Many from One.”



Filter may not appear exactly as picture.

www.sinclaire.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinclaire.com	salesuk@sinclaire.com	salesla@sinclaire.com	salescan@sinclaire.com
Product Specification Sheet		FR20107-2	Issue: 115	Dated: 22-08-16

Electrical Specifications


Frequency Range	MHz	132 to 150
Input VSWR (max)		1.5:1
Impedance	Ω	50
Average Power Input (max)	W	400
Input Connectors		N-Female
Output Connectors		N-Female
Notch attenuation (max)	dB	25

Mechanical Specifications

Width	in (mm)	7 (178)
Depth	in (mm)	7 (178)
Length/ Height	in (mm)	35 (889)
Finish		chromate conversion
Weight	lbs (kg)	11 (4.99)
Actual shipping weight	lbs (kg)	15 (6.81)
Shipping dimensions	in (mm)	39x9x9 (991x229x229)

Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)
-------------------	---------	--------------------------



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		FR20107-2	Issue: 115	Dated: 22-08-16