

Duplexers Low Band, Aviation, and VHF Duplexers P201 Series

## P201GR-1 Duplexer, bandpass, 4 cavity, high selectivity, rack mount, 132-150 MHz

- Extremely small frequency drift typically 0.5 ppm/degree C
- Rack-mountable

Bandpass duplexers are more suitable for extremely congested areas to relieve intermodulation from high-level mixing in receiver front ends, and to reduce transmitter spurious and overall extraneous radiation.

These duplexers are easily field-tunable. In addition, vernier tuning is provided for fine frequency adjustments. Because of carefully designed temperature compensation, frequency drift over the operating temperature range is extremely small, typically 0.5 ppm/°C. These duplexers are available in rack-mounted or cabinet configurations.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 017468		P201GR-1	Issue: 43	Dated: 14-02-17 Dated: 02-12-15
LFR 017400		Circleide commitment to product loodership mouroeult in i	and a second	Dated: 02-12-13

Sinclair's commitment to product leadership may result in improvement or change to this product Copyright © Sinclair Technologies



MHz	132 to 150	
	1.5:1	
Ω	50	
W	400	
	N-Female	
MHz	3	
dB	1.2	
dB	55	
	Ω W MHz dB	1.5:1   Ω 50   W 400   N-Female   MHz 3   dB 1.2


## **Mechanical Specifications**

Electrical Specifications

Width	in (mm)	19 (483)
Depth	in (mm)	15 (381)
Length/ Height	in (mm)	36 (914)
Finish		chemical conversion
Weight	lbs (kg)	55 (24.97)
Actual shipping weight	lbs (kg)	60 (27.24)
Shipping dimensions	in (mm)	20x19x40 (508x483x1016)
Mounting configurations		19 inch rack

## **Environmental Specifications**

Temperature range	°F (°C)	-40 to +140 (-40 to +60)



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 017468		P201GR-1	Issue: 43	Dated: 14-02-17 Dated: 02-12-15
Sinclair's commitment to product leadership may result in improvement or change to this product				

Sinclair's commitment to product leadership may result in improvement or change to this product Copyright © Sinclair Technologies