


Intermod Supression Panels Low Band, Aviation, and VHF IM Suppression Pannels PC2 Series

A Norsat Company in Norsat

PC2113 I.M. Suppression panel, rack mount, single stage isolator, 60 watt load, 132-174 MHz

- Single stage isolator with 60 Watt load provides 35 dB (typ) isolation
- Can be tuned over the 132-174 MHz band and comes with built-in harmonic filters
- · Compact design shipped precisely tuned to customer specified frequency

Sinclair's PC series panels incorporate high performance single- or dual-stage isolators with various load terminations and Sinclair-built harmonic filters. These compact units offer optimum intermodulation control in a 19-inch rack mounted configuration. They are shipped precisely tuned to customer specified frequency, and exhibit 25 dB or 50 dB isolation when equipped with single- or dual-stage isolators respectively. Various load configurations are available depending on system power level and VSWR protection required.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Product Specification Sheet EPR 015906

PC2113

Issue: 3 Dated: 18-06-15 Dated: 16-06-15




Intermod Supression Panels Low Band, Aviation, and VHF IM Suppression Pannels **PC2 Series**

A Norsat Company in Norsat

Frequency Range	MHz	132 to 174
Bandwidth	MHz	5
VSWR (max)		1.25:1
Insertion loss (typ) Tx to Ant	dB	0.4
Isolation (typ)	dB	35
Average Power Input (max)	W	125
Connectors		N-Female
Insertion loss (max) Tx to Ant	dB	0.6
Isolation (min)	dB	25

Mechanical Specifications			
Width	in (mm)	19 (483)	
Depth	in (mm)	9.13 (232)	
Length/ Height	in (mm)	1.75 (44)	
Actual Shipping weight	lbs (kg)	20 (9.08)	
Shipping dimensions	in (mm)	19x26x7 (483x660x178)	

Environmental Specifications			
Temperature range	°F (°C)	-22 to +140 (-30 to +60)	



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification EPR 015906	Sheet	PC2113	Issue: 3	Dated: 18-06-15 Dated: 16-06-15

Copyright © Sinclair Technologies