


Intermod Supression Panels UHF and Tetra IM Suppression Pannels PC3 Series

PC3112 I.M. Suppression panel, rack mount, single stage isolator, 30 Watt load, 406-512 MHz

- High performance single stage isolator provide 35 dB isolation
- Comes with built-in harmonic filter that provides 40 dB rejection at 2nd harmonic
- Compact design precisely tuned to customer specified frequency

Sinclair's PC series panels incorporate high performance single- or dual-stage isolators with various load terminations and Sinclair-built harmonic filters. These compact units offer optimum intermodulation control in a 19-inch rack mounted configuration. They are shipped precisely tuned to customer specified frequency, and exhibit 35 dB or 75 dB isolation when equipped with single- or dual-stage isolators respectively. Various load configurations are available depending on system power level and VSWR protection required.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		PC3112	Issue: 97	Dated: 18-06-15



A	Norsat	Company	n	INOTSAL International Inc.

Electrical Specifications			
Frequency Range	MHz	406 to 512	
Bandwidth	MHz	12	
VSWR (max)		1.25:1	
Average Power Input (max)	W	125	
Connectors		N-Female	
Insertion loss (max) Tx to Ant	dB	0.5	
Isolation (min)	dB	25	

Mechanical Specifications

Width	in (mm)	19 (483)	
Depth	in (mm)	9.13 (232)	
Length/ Height	in (mm)	1.75 (44)	
Actual Shipping weight	lbs (kg)	20 (9.08)	
Shipping dimensions	in (mm)	26x19x7 (660x483x178)	

Environmental Specifications

Temperature range °F (°C) -22 to +140 (-30 to +60)	Temperature range	°F (°C)	-22 to +140 (-30 to +60)	

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specificatio	n Sheet	PC3112	Issue: 97	Dated: 18-06-15