


Intermod Supression Panels
UHF and Tetra IM Suppression Pannels
PC3 Series

PC3113 I.M. Suppression panel, rack mount, single stage isolator, 60 Watt load, 406-512 MHz

- High performance single stage isolator provide 35 dB isolation
- Comes with built-in harmonic filter that provides 40 dB rejection at 2nd harmonic
- · Compact design precisely tuned to customer specified frequency

Sinclair's PC series panels incorporate high performance single- or dual-stage isolators with various load terminations and Sinclair-built harmonic filters. These compact units offer optimum intermodulation control in a 19-inch rack mounted configuration. They are shipped precisely tuned to customer specified frequency, and exhibit 35 dB or 75 dB isolation when equipped with single- or dual-stage isolators respectively. Various load configurations are available depending on system power level and VSWR protection required.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		PC3113	Issue: 97	Dated: 18-06-15



Intermod Supression Panels
UHF and Tetra IM Suppression Pannels
PC3 Series

A Norsat Company Norsat

Frequency Range	MHz	406 to 512
Bandwidth	MHz	12
VSWR (max)		1.25:1
Average Power Input (max)	W	125
Connectors		N-Female
Insertion loss (max) Tx to Ant	dB	0.5
Isolation (min)	dB	25
Mechanical Specifications		
•	in (mm)	19 (483)
Width	in (mm) in (mm)	19 (483) 9.13 (232)
Mechanical Specifications Width Depth Length/ Height	\ /	()
Width Depth	in (mm)	9.13 (232)
Width Depth Length/ Height Actual Shipping weight	in (mm) in (mm) lbs (kg)	9.13 (232) 1.75 (44) 20 (9.08)
Width Depth Length/ Height	in (mm) in (mm)	9.13 (232) 1.75 (44)
Width Depth Length/ Height Actual Shipping weight	in (mm) in (mm) lbs (kg)	9.13 (232) 1.75 (44) 20 (9.08)

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		PC3113	Issue: 97	Dated: 18-06-15