

**Intermod Supression Panels** 700-1000 MHz IM Suppression Pannels **PC4 Series** 

A Norsat Company in Norsat

PC4214 I.M. Suppression panel, rack mount, dual stage isolator, 30+125 Watt loads, 806-890 MHz

- Dual stage isolator with 30+125 Watt loads provides 75 dB (typ) isolation
- Can be tuned over the 806-890 MHz band and comes with built-in harmonic filters
- · Compact design shipped precisely tuned to customer specified frequency

Sinclair's PC series panels incorporate high performance single- or dual-stage isolators with various load terminations and Sinclair-built harmonic filters. These compact units offer optimum intermodulation control in a 19-inch rack mounted configuration. They are shipped precisely tuned to customer specified frequency, and exhibit 25 dB or 50 dB isolation when equipped with single- or dual-stage isolators respectively. Various load configurations are available depending on system power level and VSWR protection required.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		PC4214	Issue: 4	Dated: 31-08-15



## **Intermod Supression Panels** 700-1000 MHz IM Suppression Pannels **PC4 Series**

\*1:3% of center frequency.

Notes

A Norsat Company Norsat

Electrical Specifications			
Frequency Range	MHz	806 to 960	
Bandwidth	MHz	30	*-
VSWR (max)		1.25:1	
Isolation (typ)	dB	75	
Average Power Input (max)	W	150	
Connectors		N-Female	
Insertion Loss (typ) Tx to Ant	dB	0.6	
Insertion Loss (max) Tx to Ant	dB	0.9	
Isolation (min)	dB	50	
Mechanical Specifications Width	in (mm)	19 (483)	
Depth	in (mm)	9.13 (232)	
Length/ Height	in (mm)	3.5 (89)	
Weight	lbs (kg)	20 (9.08)	
Shipping dimensions	in (mm)	19x26x7 (483x660x178)	
Environmental Specifications			
Temperature range	°F (°C)	-22 to +140 (-30 to +60)	
	\ - /	, ,	

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 018875		PC4214	Issue: 4	Dated: 31-08-15 Dated: 31-08-15

Page 2/2