


A Norsat Company in Norsat

PH4040E-12 Bandpass Preselector, Res-Lok, 12 MHz bandwidth, 4 cavity, 763-805 MHz

- · Rack, wall and floor mounting options
- · Res-Lok construction reduces inter-cavity cabling
- · Can also be used as transmitter filter

This series is available in various pass band widths and provides superior attenuation of out of band signals while maintaining relatively low insertion loss. This highly versatile Res-Lok™ construction preselector can be rack, wall or floor mounted to suit any system need. The 'PH' series can also be used as a transmitter filter. These filters are field re-tunable allowing efficient reuse.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		PH4040E-12	Issue: 13	Dated: 08-10-13



Preselector Filters 700-1000 MHz Preselectors PH4040 Series

A Norsat Company in Norsat

Electrical Specifications			
Frequency Range	MHz	763 to 805	
Input VSWR (max)		1.5:1	
Impedance	Ω	50	
Number of Cavities		4	
Average Power Input (max)	W	400	
Input Connectors		N-Female	
Output Connectors		N-Female	
Approx Bandwidth @ 50 dB	MHz	60	
Bandwidth at specified insertion loss	MHz	12	
Insertion loss (max) Tx to Ant	dB	0.5	
Mechanical Specifications Depth	in (mm)	8.5 (216)	
Length/ Height	in (mm)	4.17 (106)	
Width	in (mm)	19 (483)	
Weight	lbs (kg)	6.5 (2.95)	
Actual Shipping weight	lbs (kg)	10 (4.54)	
Shipping dimensions	in (mm)	19x7x18 (483x178x457)	
Mounting configurations		19 inch rack	
iviounting configurations		19 IIICH IACK	
Environmental Specifications			
Temperature range	°F (°C)	-22 to +140 (-30 to +60)	

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 018326		PH4040E-12	Issue: 13	Dated: 08-10-13 Dated: 27-09-13

Sinclair's commitment to product leadership may result in improvement or change to this product Copyright © Sinclair Technologies