


A Norsat Company in Norsat

## Q301GR-4 Q-Circuit 6 Cavity Base Station Duplexer, Rack Mountable, 420-450 MHz

- High attenuation at extremely close frequency spacings in 420-450 MHz band
- · Quasi bandpass response suppresses spurious and side-band transmitter noise
- · Easy rack-mounted configuration.

The Q-301G base station duplexer utilizes Sinclair's Q-circuit design in a 6-cavity configuration to provide very high attenuation at extremely close frequency separation in the 406-512 MHz band. This design provides a quasi-bandpass response, resulting in suppression of spurious and side-band transmitter noise between and adjacent to the duplex frequencies. The Q-302GR is a rack-mounted configuration.

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com






A Norsat Company in Norsat



**Electrical Specifications** 420 to 450 Frequency Range MHz Number of cavites Tx Side 3 Number of Cavities Rx Side 3 Input VSWR (max) 1.5:1 Impedance Ω 50 Isolation Rx carrier suppression at Tx (min) 100 dΒ Isolation Tx noise suppression at Rx (min) dB 100 Average Power Input (max) W 250 MHz 0.7 Frequency separation (min) dΒ 2.2 Insertion loss Rx to antenna (max) dΒ 2.2 Insertion loss Tx to antenna (max)

Mechanical Specifications					
Depth	in (mm)	15 (381)			
Length/ Height	in (mm)	35 (889)			
Width	in (mm)	19 (483)			
Weight	lbs (kg)	60 (27.24)			
Actual Shipping weight	lbs (kg)	90 (40.86)			
Shipping dimensions	in (mm)	20x16x21 (508x406x533)			
Mounting configurations		19 inch rack			

Environmental Specifications			
Temperature range	°F (°C)	-40 to +140 (-40 to +60)	



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Sinclair's commitment to product leadership may result in improvement or change to this product

Copyright © Sinclair Technologies