

Duplexers UHF and Tetra Duplexer Q3330C Series

Q3330C-2

Duplexer, Q-Circuit, Res-Lok, compact, 6 cavity, rack mount, 450-470 MHz

Also referred as: Q3330C*2

- Typical minimum isolation of 85 dB at maximum insertion loss of 1.2 dB
- 5 MHz minimum Tx-Rx separation.
- · Rugged Res-Lok design reduces inter-cavity cabling

Similar to the Q3220C duplexer, this very compact unit provides enhanced isolation characteristics through the addition of two cavities. The entire 6 cavity duplexer mounts in a standard 19 inch rack, occupying only 4.17 inches of vertical space.

Proud Partner of the iBwave Component Database.








A Norsat Company in Norsat



Electrical Specifications			
Frequency Range	MHz	450 to 470	
Number of Cavities - Tx Side		3	
Number of Cavities - Rx Side		3	
Connectors		N-Female	
Input VSWR (max)		1.3:1	
Insertion Loss (max) Tx to Ant	dB	1.2	
Impedance	Ω	50	
Average Input Power (max)	W	350	
Frequency separation (min)	MHz	5	
Isolation (min)	dB	85	

Width	in (mm)	19 (483)
Depth	in (mm)	16.3 (414)
_ength/ Height	in (mm)	4.2 (107)
Finish		chemical conversion
Weight	lbs (kg)	16 (7.26)
Mounting configurations		19 inch rack
Actual shipping weight	lbs (kg)	25 (11.35)
Shipping dimensions	in (mm)	19x8x22 (483x203x559)

Environmental Specifications		
Temperature range	°F (°C)	-40 to +140 (-40 to +60)



Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com
Product Specification EPR 015884	n Sheet	Q3330C-2	Issue: 46	Dated: 02-11-20 Dated: 27-09-13

Sinclair's commitment to product leadership may result in improvement or change to this product

Copyright © Sinclair Technologies