**Duplexers UHF** and Tetra Duplexer Q3330C Series

Q3330C-4

Duplexer, Q-Circuit, Res-Lok, compact, 6 cavity, rack mount, 470-512 MHz

Also referred as: Q3330C\*4

- Typical minimum isolation of 85 dB at maximum insertion loss of 1.2 dB
- 5 MHz minimum Tx-Rx separation.
- · Rugged Res-Lok design reduces inter-cavity cabling

Similar to the Q3220C duplexer, this very compact unit provides enhanced isolation characteristics through the addition of two cavities. The entire 6 cavity duplexer mounts in a standard 19 inch rack, occupying only 4.17 inches of vertical space.

Proud Partner of the iBwave Component Database.



Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com
Product Specification Sheet		Q3330C-4	Issue: 46	Dated: 02-11-20







**Electrical Specifications** 470 to 512 Frequency Range MHz Connectors N-Female Input VSWR (max) 1.3:1 dΒ Insertion Loss (max) Tx to Ant 1.2 50 Impedance Ω Average Input Power (max) W 350 Frequency separation (min) MHz 5 dΒ 85 Isolation (min) **Mechanical Specifications** 19 (483) in (mm) Depth in (mm) 16.3 (414) Length/ Height in (mm) 4.2 (107) Finish chemical conversion Weight lbs (kg) 16 (7.26) Mounting configurations 19 inch rack Actual shipping weight lbs (kg) 25 (11.35) Shipping dimensions in (mm) 19x8x22 (483x203x559)

		· ·	
<b>Environmental Specifications</b>			
Temperature range	°F (°C)	-40 to +140 (-40 to +60)	

Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com
Product Specification Sheet EPR 015884		Q3330C-4	Issue: 46	Dated: 02-11-20 Dated: 02-11-20