

SC251-HF3LDF(D00-G4) Collinear omni antenna, 3.5 dBd gain, low PIM, PIP rated, HD, 148-168 MHz

- Wideband 3.5 dBd gain collinear omni antenna
- 500W power handling with low PIM and high PIP rating
- Rugged fiberglass radome provides superior environmental protection
- 0, 2, 4, or 6 degrees of electrical downtilt available

**A side mounting kit is Mandatory when offset mounting the antenna. The SMK-345-A7 for Offset Side Mount is available separately.**

The SC251-HL is a 3.5dBd collinear omni featuring low passive intermod performance with single or dual port configuration option available. Fabricated using durable components, this series of antennas is designed for ease of installation. The foam wrapped brass construction provides a light and durable structure housed in a UV protected fiberglass radome ensuring superior resistance to harsh environmental conditions. This family is fabricated to meet the most stringent wind and ice loading requirements.

Due to its wide band and high average power and PIP power handling capability, this antenna is ideally suited for VHF trunking applications or multi-channel operations.

The reliability and durability of this antenna makes it suitable for mission critical applications such as public safety and law enforcement.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
<b>Telephone</b>	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
<b>E-mail</b>	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

#### Electrical Specifications


Frequency Range	MHz	148 to 168
Bandwidth	MHz	20
Connector		7/16 DIN-Female
Gain (nominal)	dBd (dBi)	3.5 (5.6)
Input VSWR (max)		1.5:1
Polarization		vertical
Impedance	Ω	50
Pattern		Omni- directional
Vertical beamwidth (typ)	degrees	22
Average Power Input (max)	W	500
Passive intermod. (2x20W, 3rd ord.)	dBc	-150
Lightning protection		DC ground
PIP(KW, max)		25
Electrical tilt (available)		0, 2, 4, or 6 degrees

#### Ordering Information

Clamps must be ordered separately

#### Mechanical Specifications

Width	in (mm)	5 (127)
Depth	in (mm)	5 (127)
Length/ Height	in (mm)	200 (5080)
Base pipe diameter	in (mm)	5 (127)
Base pipe mounting length	in (mm)	26 (660)
Radome material		fiberglass (UV protected)
Weight	lbs (kg)	74 (33.6)
Weight iced (1/2" ice)	lbs (kg)	126 (57.2)
Weight iced (1" ice)	lbs (kg)	189 (85.81)
Mounting Hardware (Optional)		Clamp006C
Actual shipping weight	lbs (kg)	102 (46.31)
Shipping dimensions	in (mm)	212x6x6 (5385x152x152)
Number of ports		1
Mounting configurations		Universal mount
Recommended For Offset Side Mount:		SMK-345-A7
Radome Colour		Light Blue



#### Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)
Wind Loading Area (Flat Plate Equivalent)	ft² (m²)	4.3 (0.4)
Wind Loading Area (1/2" ice)	ft² (m²)	5.2 (0.48)
Wind Loading Area (1" ice)	ft² (m²)	6.1 (0.57)
Rated wind velocity (no ice)	mph (km/h)	225 (362)
Rated wind velocity (1/2" radial ice)	mph (km/h)	195 (314)
Rated wind velocity (1" radial ice)	mph (km/h)	180 (290)
Lateral thrust (100 mph No Ice)	lbs (N)	168 (747.3)
Bending moment (100 mph No Ice)	ft-lbs (Nm)	1008 (1360.8)
Tip deflection (100 mph No Ice)	degrees	0.8

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com