

SC34A-ST2SNF(DXX) Aurora™ collinear omni antenna, 10 dBd, 410-430 MHz

- High gain, omni-directional antenna
- Patent-pending Aurora™ design for outstanding performance
- 20 MHz fully operational bandwidth with highly consistent RF performance
- Rugged design and UV protected radome for harsh environment

The Aurora™ SC family is Sinclair's next-generation of public safety collinear antennas. The patent-pending design utilizes cutting-edge yet field-proven technology to deliver an unparalleled combination of highly stable RF pattern, higher gain, and wider bandwidth.

Specifically, the SC34A series collinear omni-directional antenna offers 10 dBd gain in 20 MHz (typ) band splits covering the 380-512 MHz UHF frequency range. This antenna is designed for a high degree of operational reliability in extreme wind, ice, and corrosive conditions. Its relatively low mass and small wind-loading profile makes it easy to install. The antenna is fully DC grounded on all elements for the ultimate lightning protection and dissipation of static noise. Severe weather conditions have been fully considered in the overall design, its rugged UV resistant fiberglass radome for harsh environment, carefully designed internal supporting structure, certified long-life components, extra-long base pipe for high wind rating, etc.

When ordering, please refer to the chart below for the model number. Downtilt configurations are subject to various list price. Other connectors and pigtail terminated types are also available, please contact your Sinclair Sales Representative or Customer Service Representative for more information.

Model Number	Gain(dBd)	Downtilt
SC34A-ST2SNF(D00)	10	0°
SC34A-ST2SNF(D03)	10	3°
SC34A-ST2SNF(D06)	10	6°



www.sinctech.com

Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com
Product Specification Sheet		SC34A-ST2SNF(DXX)	Issue: 3	Dated: 04-09-20

### Electrical Specifications

Frequency Range	MHz	410 to 430
Bandwidth	MHz	20
Connector		N-Female *1
Gain (nominal)	dBd (dBi)	10 (12.1)
Input VSWR (max)		1.5:1
Polarization		vertical
Impedance	Ω	50
Pattern		Omni- directional
Vertical beamwidth (typ)	degrees	7.5
Average Input Power (max)	W	500
Number of ports		1
Lightning protection		DC ground
Electrical tilt (available)		0, 3, 6 degrees

### Notes


- \*1 : Flange mount
- \*2 : Qty:2

### Mechanical Specifications

Width	in (mm)	2.88 (73)
Depth	in (mm)	2.88 (73)
Length/ Height	in (mm)	249 (6325)
Base pipe diameter	in (mm)	2.88 (73)
Weight	lbs (kg)	41 (18.61)
Weight iced (1/2" ice)	lbs (kg)	79 (35.87)
Mounting Hardware (Optional)		Clamp005, or Clamp005X *2
Recommended For Offset Side Mount:		SMK-225-A3-T5 or SMK-225-A7-T5
Actual shipping weight	lbs (kg)	76 (34.5)
Shipping dimensions	in (mm)	262x4.5x4.5 (6655x114x114)

### Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)
Wind Loading Area (Flat Plate Equivalent)	ft² (m²)	2.8 (0.26)
Wind Loading Area (1/2" ice)	ft² (m²)	3.9 (0.36)
Rated wind velocity (no ice)	mph (km/h)	135 (217)
Rated wind velocity (1/2" radial ice)	mph (km/h)	110 (177)
Lateral Thrust (100 mph No Ice)	lbs (N)	106 (471.5)
Bending moment (100 mph No Ice)	ft-lbs (Nm)	893 (1205.6)
Tip deflection (100 mph No Ice)	degrees	6.7



Elevation

Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com
Product Specification Sheet		SC34A-ST2SNF(DXX)	Issue: 3	Dated: 04-09-20