

SC432T-SF6LDF(D06-I30-G06) Triple collinear omni, 6 dBd, 6° DT, low PIM, 746-869 MHz

- Triple port collinear antenna with 30 dB port-to-port isolation with 6 dBd gain.
- 6 degrees of downtilt
- Designed to operate in extreme environmental conditions.
- Low PIM

**Recommend SMK-335-A3 or SMK-335-A7 for Offset Side Mount.  
Available from Sinclair separately.**

Sinclair SC432T antenna is a tripple port antenna that comes with outstanding isolation which means precious tower space can be saved. Designed for multi-channel systems, it features with low intermodulation products and highly rated average power. The SC432 series antennas are enclosed in a rugged, UV protected fiberglass radome designed to withstand severe wind and ice conditions.

Other options are also available, such as higher or lower gain. Please contact Sinclair for details.



www.sinctech.com

Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com

### Electrical Specifications

Frequency Range	MHz	746 to 869
Connector		7/16 DIN-Female
Gain (nominal)	dBd (dBi)	6 (8.1)
Input VSWR (max)		1.5:1
Polarization		vertical
Impedance	Ω	50
Pattern		Omni-directional
Vertical beamwidth (typ)	degrees	12.7
Average Input Power (max)	W	500
Isolation between sections (nom)	dB	30
Passive intermod. (2x20W, 3rd ord.)	dBc	-150
Lightning protection		DC ground
Electrical tilt (available)		0,2,4, or 6 degrees

### Notes

- \*1 : Qty 2
- \*2 : Not included.

### Mechanical Specifications

Width	in (mm)	3.5 (89)
Depth	in (mm)	3.5 (89)
Length/ Height	in (mm)	214.5 (5448)
Base pipe diameter	in (mm)	3.5 (89)
Base pipe mounting length	in (mm)	30 (762)
Radiating element material		brass
Radome material		fiberglass (UV protected)
Weight	lbs (kg)	43 (19.52)
Weight iced (1/2" ice)	lbs (kg)	82 (37.23)
Mounting configurations		upright
Mounting Hardware (Optional)		Clamp006B
Kit for Offset Side Mount (straight tower leg)		SMK-335-A3 or SMK-335-A7
Actual shipping weight	lbs (kg)	75 (34.05)
Shipping dimensions	in (mm)	240x6x6 (6096x152x152)

### Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)
Wind Loading Area (Flat Plate Equivalent)	ft² (m²)	3.06 (0.28)
Wind Loading Area (1/2" ice)	ft² (m²)	4.05 (0.38)
Rated wind velocity (no ice)	mph (km/h)	155 (250)
Rated wind velocity (1/2" radial ice)	mph (km/h)	130 (209)
Lateral Thrust (100 mph No Ice)	lbs (N)	121 (538.2)
Bending moment (100 mph No Ice)	ft-lbs (Nm)	795 (1073.3)
Tip deflection (100 mph No Ice)	degrees	3.2

Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com