

SD314-HF2P4SNM(D10) 4 dipole, 8.5 dBd, offset, 10° DT, HD, 406-512 MHz

- Covers entire 406-512 MHz frequency range
- 8.5 dBd gain with offset pattern and 10 degrees of downtilt
- Heavy duty and 150W power handling.
- Can be top or side mounted (Universal mount)

**Recommend SMK-125-A3 side mount kit when side mounting antenna.
Available from Sinclair separately.**

The SD314-H series is an extremely rugged 4-bay exposed dipole antenna designed for applications where moderate gain is required. These premium-quality antennas are well suited to public safety applications.

The design of these antennas provides for coverage between 370 to 512 MHz in 2 sub bands, 370-460 MHz and 406-512 MHz for private mobile networks, public safety and public security networks.



www.sinctech.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Electrical Specifications

Frequency Range	MHz	406 to 512	*1
Connector		N-Male	
Gain (nominal)	dBd (dBi)	8.5 (10.6)	
Input VSWR (max)		1.5:1	
Polarization		vertical	
Impedance	Ω	50	
Pattern		Offset	
Horizontal beamwidth (typ)	degrees	222	
Vertical beamwidth (typ)	degrees	16	
Average Power Input (max)	W	200	
Lightning protection		DC ground	
Electrical tilt (available)		0,2,4,6,8, or 10 degrees	

Notes

- *1 : F1=370-460MHz, F2=406-512MHz.
- *2 : Qty 2
- *3 : Flat plate equivalent.

Mechanical Specifications

Width	in (mm)	12 (305)	
Depth	in (mm)	3.5 (89)	
Length/ Height	in (mm)	114 (2896)	
Base pipe diameter	in (mm)	2.38 (60)	
Base pipe mounting length	in (mm)	36 (914)	
Radiating element material		aluminum	
Base pipe material		aluminum	
Weight	lbs (kg)	23 (10.44)	
Mounting Hardware (Optional)		Clamp005, Clamp015, Clamp130, or Clamp125U	*2
Actual shipping weight	lbs (kg)	35 (15.89)	
Shipping dimensions	in (mm)	118x4x20 (2997x102x508)	
Mounting configurations		Universal Mount	
Recommended For Offset Side Mount:		SMK-125-A3	

Ordering Information

Clamps must be ordered separately.

Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)	
Wind Loading Area (Flat Plate Equivalent)	ft² (m²)	1.73 (0.16)	
Wind Loading Area (1/2" ice)	ft² (m²)	4.38 (0.41)	*3
Rated wind velocity (no ice)	mph (km/h)	185 (298)	
Rated wind velocity (1/2" radial ice)	mph (km/h)	150 (242)	
Lateral thrust (100 mph No Ice)	lbs (N)	77 (342.5)	
Torsional moment (100 mph No Ice)	ft-lbs (Nm)	11 (14.9)	
Bending moment (100 mph No Ice)	ft-lbs (Nm)	132 (178.2)	

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com