

SD6035(ABK) Comshell antenna, 4.8 dBd, black anodized, 138-174 MHz

- Covers 138-174 MHz at 2:1 VSWR
- Mounting: Comshel mount with W108 clamps and SRX0013 coupler
- Black anodized, MIL A-8625, 25-30 microns

www.sinctech.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		SD6035(ABK)	Issue: 91	Dated: 15-04-15

Electrical Specifications

Frequency Range	MHz	138 to 174
Bandwidth	MHz	36
Gain (nominal)	dBd (dBi)	4.8 (6.9)
VSWR (max)		2:1
Polarization		vertical
Impedance	Ω	50
Input Connectors		N-Male
Power Rating	W	250

Notes

*1 : Qty 2 required

Mechanical Specifications

Depth	in (mm)	5 (127)
Length/ Height	in (mm)	107 (2718)
Width	in (mm)	26.1 (663)
Weight	lbs (kg)	17.5 (7.95)
Mounting hardware		W108 clamps *1

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		SD6035(ABK)	Issue: 91	Dated: 15-04-15