

**SHA411-SF2S(XX)** Concealed bumper mount antenna, 40-70 MHz B.W., 806-869 MHz

- Completely hidden-does not need any existing vehicle antennas
- Wide band with 40 to 70 MHz bandwidth depending on the vehicle
- Easy installation and tuning for optimum performance and durability in a wide variety of vehicles
- Applicable for both covert and overt law enforcement vehicles

Sinclair's patented concealed bumper mount antennas SHA411 series are designed for law-enforcement vehicles. The antennas are hidden inside the bumper and weatherproofed. The bumper covers must be plastic. Featuring a unique modular design that integrates all the components into a compact waterproof housing making it possible to install the antenna with minor modifications to the bumper. These antennas are mounted with simplicity and ease beneath the bumper cover thereby totally concealing the antenna from sight. A fine-tuning adjustment permits performance optimization during installation.

Attention: The antenna must be installed properly following the installation instruction. For some unique vehicles, please contact Sinclair sales representative or CSR for custom designs to achieve the optimum performance. Dual antennas (one in the front bumper and one in the rear) can be used for better Omni coverage. The antenna must be installed and weatherproofed properly following the installation instruction. The phasing harness and the joints to the two SHA411 antennas are not weatherproofed, so they must be placed inside the vehicle.



The antenna is integrated with a 24 feet RG58 feed cable. See below chart for ordering information:

Model Name	Connector
SHA411-SF2SNM	N-male, loose
SHA411-SF2SUM	UHF-male, loose
SHA411-SF2SQM	QMA-male, loose

Note: the connector is provided loose for ease of cable running inside the vehicle and will need to be crimped on by the customer. Other connectors and cable configuration options are available. Contact your Sinclair Sales Representative or Customer Service Representative for details.

### Application Notes

- Bandwidth is dependent upon the type of vehicle and mounting position.

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
<b>Telephone</b>	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
<b>E-mail</b>	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

### Electrical Specifications

Frequency Range	MHz	806 to 869	
Bandwidth (Min-Max)	MHz	40 to 70	*1
Connector		Various options avail.	*2
Gain (nominal)	dBd (dBi)	unity (2.1)	
Input VSWR (max)		2:1	
Polarization		vertical	
Impedance	Ω	50	
Pattern		Omni- directional	
Average Input Power (max)	W	150	

### Notes

- \*1 : Depending on vehicle
- \*2 : See previous page for detail.

### Mechanical Specifications

Width	in (mm)	3 (76)
Depth	in (mm)	2 (51)
Length/ Height	in (mm)	10.5 (267)
Mounting hardware		#8-32 screws (4)
Shipping dimensions	in (mm)	9x14x5 (229x356x127)

### Ordering Information

Please contact Sinclair CSR for your requirement on dual antennas (one in the front bumper and one in the rear)

### Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)
-------------------	---------	--------------------------

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
<b>Telephone</b>	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
<b>E-mail</b>	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com