

SM202-SF1/SWBSNF(FXXXX) High performance, 2 MHz B.W. for VHF, 138-174 MHz / 350-2700 MHz

- Covers full 350-2700 MHz and 138-174 MHz with 2 MHz (typ) bandwidth
- A maximum height of 4 1/4 inches complies with restriction for locomotives and other vehicles
- Black weather resistant and fire rated radome provides excellent environmental protection

**To perform properly, the antenna needs to be installed on a metal surface with minimum size of 36x48 in.  
 Complies with IEC 68 standards**



The SM202 series antenna is intended primarily for wireless coverage in transportation applications. This antenna is designed for ease of installation and minimal visual impact. It features a low-profile multiple band radiating element incorporated in a low profile and unobtrusive black housing that is perfect for mounting to a typical metal vehicle rooftop.

The standard SM202 antenna comes with two ports, one for VHF narrow band and one for UHF and above frequency range wide band uses. The wide band port covers full frequency range of 350-2700 MHz, can be used for TETRA400, TETRA800, trunking systems, governmental services, Car telephone network C, NMT 450, TV, DVB, NMT, TACS, AMPS, TDMA, CDMA, PDC, GSM900, GSM1800, GSM1900, EDGE, WCDMA, CDMA2000, UMTS, PHS, DECT and PCS cellular, LTE and WiFi. This port can support multiple systems simultaneously with Sinclair's cross band combining solutions. It can also be expanded for multiple uses quickly without interference with the existing service. Please contact Sinclair customer service for the cross band combining solutions. The narrow band port covers 138-230 MHz in 3 sub-bands with 2 MHz typical bandwidth, which is tuned to customer specified center frequency.

The antenna is fed by two RG303 pigtailed with N female connectors. Other connector options are also available.

**Application Notes**

- SM202-SF1/SWBSNF(Fxxxx): N female connector, VHF center frequency Fxxxx, no GPS. Fxxxx=F1610 for 161.0 MHz.

www.sinctech.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

### Electrical Specifications

Frequency Range 1 (F1)	MHz	138 to 174	
Bandwidth (F1)	MHz	2	*1
Frequency Range 2 (F2)	MHz	350 to 2700	
Bandwidth (F2)	MHz	2350	*2
Connector		N-Female	*3
Gain (nominal)	dBd (dBi)	unity (2.1)	
Input VSWR (max)		1.5:1	
Polarization		vertical	
Impedance	Ω	50	
Pattern		Omni- directional	
Average Power Input (max)	W	200	*4
Lightning protection		DC ground	

### Notes

- \*1 : 1 MHz on low side of band, 2.5 on the high side.
- \*2 : VSWR=1.5:1(typ) for 380-2700MHz; VSWR=2:1(typ) for 360-380 MHz; VSWR=2.5:1(typ) for 350-360 MHz.
- \*3 : Other options available such as N male, BNC male and female, and TNC male and female.
- \*4 : Per port
- \*5 : Maximum footprint
- \*6 : Maximum footprint

### Mechanical Specifications

Width	in (mm)	11.5 (292)	*5
Depth	in (mm)	20.88 (530)	*6
Height	in (mm)	4 (102)	
Radome material		UV stabilized ABS	
Weight	lbs (kg)	7.21 (3.27)	
Actual shipping weight	lbs (kg)	11.2 (5.08)	
Shipping dimensions	in (mm)	26x19x7 (660x483x178)	
Ground Plane (min)	in (mm)	36x48	
Radome Colour		Black	

### Ordering Information

Please specify VHF center frequency, and connector type at time of order

### Environmental Specifications

Horizontal Wind Resistance		5.03 lb @ 100 mph
Temperature range	°F (°C)	-40 to +140 (-40 to +60)
Wind Loading Area (Flat Plate Equivalent)	ft² (m²)	0.2 (0.02)

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
<b>Telephone</b>	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
<b>E-mail</b>	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com