

Antennas Low Band, Aviation, and VHF Antennas ST221 Series

ST221-SF1SNF(FXXXX)

Mobile omni, 0 dBd, 2.5 MHz B.W., N-Female, 138-163 MHz

Also referred as: EXCAL221NF-XXXX

- · Low profile for a wide range of mobile applications
- Cast aluminum
- · 2.5 MHz Bandwidth
- · Applications include: trains, taxis, police cars, emergency vehicles, buses and trucks

## A minimum 62" x 42" ground plane is required.

Sinclair's Excaliber ST221 series of antennas are low profile antennas designed for a wide range of mobile applications. Their design renders them relatively inconspicuous and resistant to damage. They have become a North American standard antenna for railroad locomotive service.



A minimum 62" x 42" ground plane is required.

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Draduat Cassification	- Chast	CTOOL CELCNE/EVVVV	leave. 2	Datad: 14 10 16

Sinclair's commitment to product leadership may result in improvement or change to this product

Copyright © Sinclair Technologies



## Antennas Low Band, Aviation, and VHF Antennas ST221 Series

A Norsat Company in Norsat

Electrical Specifications					
Frequency Range	MHz	138 to 163			
Bandwidth	MHz	2.5			
Connector		N-Female			
Gain (nominal)	dBd (dBi)	unity (2.1)			
Input VSWR (max)		1.5:1			
Polarization		vertical			
Impedance	Ω	50			
Pattern		Omni-directional			
Average Power Input (max)	W	300			
Lightning protection		DC ground			


**Mechanical Specifications** 2.2 (56) Width in (mm) Depth 24.5 (622) in (mm) Length/ Height 4 (102) in (mm) Actual shipping weight 6(2.72)lbs (kg) 3x5x25 (76x127x635) Shipping dimensions in (mm) Ground Plane (min) 62x42 in (mm) Mounting hardware Supplied

**Environmental Specifications** -40 to +140 (-40 to +60) Temperature range °F (°C)

## **Ordering Information**

Specify exact frequency at time of order. For frequency 160.8 MHz, please use model number ST221-SF1SNF(F1610). The part number should be to the nearest 0.5 MHz.

UHF-Female connector also available.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 018350		ST221-SF1SNF(FXXXX)	Issue: 3	Dated: 14-12-16 Dated: 25-01-16