

ST221-SF3SNF(FXXXX-LP) Mobile omni, 0 dBd, Low Profile, 2 MHz B.W., Band III, 190-225 MHz

- 2 MHz bandwidth in the Band III
- Can be used for a wide range of mobile applications
- Made from cast aluminum
- Highly durable and resistant to damage

**A minimum 36" x 36" ground plane is required.**

The Excaliber ST221 antenna has become a North American standard for railroad and locomotive applications. The new lower profile version of this antenna, ST221-LP series, is now available for 159.5 MHz to 225 MHz range. The F1 model can be tuned over 159.5-163.5 MHz, F2 model 170-195 MHz, and the F3 model 190-225 MHz. With a footprint that is the same as the classic Excaliber ST221 antenna, but with the height being just 2.5 inches (6.35 cm) instead of 4.0 inches (10.16 cm), the ST221-LP is primarily designed for applications where antennas must be installed in an extremely low profile radio compartment or an antenna radome located on the vehicle's rooftop (may require retuning when installed under radome).



www.sinctech.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

### Electrical Specifications

Frequency Range	MHz	190 to 225
Bandwidth	MHz	2
Connector		N-Female
Gain (nominal)	dBd (dBi)	unity (2.1)
Input VSWR (max)		1.5:1
Polarization		vertical
Impedance	Ω	50
Pattern		Omni-directional
Average Power Input (max)	W	300
Lightning protection		DC ground

### Notes

\*1 : maximum length

### Mechanical Specifications


Width	in (mm)	2.2 (56)	
Length	in (mm)	20.5 (521)	*1
Height	in (mm)	2.5 (64)	
Weight	lbs (kg)	3.9 (1.77)	
Actual shipping weight	lbs (kg)	6 (2.72)	
Shipping dimensions	in (mm)	3x5x25 (76x127x635)	
Ground Plane (min)	in (mm)	36x36	
Mounting hardware		HK221A	

### Ordering Information

Specify frequency at time of order.

### Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)
-------------------	---------	--------------------------



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
<b>Telephone</b>	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
<b>E-mail</b>	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com