

Antennas UHF and Tetra Antennas ST321R Series

## ST321R-SF1SNF(CWH) Mobile omni, 0 dBd, 14 MHz B.W., N-female, White, 406-420 MHz

• For use in both fixed and mobile installations

- Also referred as: EXCAL321RNF\*1W • For use in the second second
  - Proven performance in harsh environments
  - Available with white or grey radome
  - Available with N-Female or BNC-Female connector

## Minimum 30" x 30" ground plane is required.

Sinclair's radome-enclosed ST321R series of antennas is designed for a variety of mobile applications: railroad locomotives, taxis, police cars, emergency vehicles, buses and trucks.

Fire retardant radome is available.



Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific	
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165	
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com	
Product Specification EPR 016270		ST321R-SF1SNF(CWH)	Issue: 11	Dated: 05-11-20 Dated: 05-11-20	
Customer Tech Manual 005665		Sinclair's commitment to product leadership may result in improvement or change to this product			



A Norsat Company 🔟 Norsat

# Antennas UHF and Tetra Antennas ST321R Series

N	ataa	
11	oles	

\*1

\*2

\*1 : Similar to 1/4 wave monopole. \*2 : Similar to 1/4 wave monopole.

#### **Mechanical Specifications**

Average Input Power (max)

**Electrical Specifications** 

Frequency Range

Bandwidth

Connector

Gain (nominal)

Polarization

Impedance

Pattern

Input VSWR (max)

Lightning protection

Width	in (mm)	3.8 (97)	
Length/ Height	in (mm)	3 (76)	
Length	in (mm)	11.8 (300)	
Radome material		ABS (white)	
Mounting hardware		Supplied	
Actual shipping weight	lbs (kg)	5 (2.27)	
Shipping dimensions	in (mm)	13x8x5 (330x203x127)	
Ground Plane (min)	in (mm)	30x30	

MHz

MHz

dBd (dBi)

Ω


W

## Ordering Information

Specify operating frequency.

#### Environmental Specifications Temperature range

°F (°C)



406 to 420

14

N-Female

unity (2.1)


1.5:1

vertical

50

Omni-directional

50 DC ground



Elevation

Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com
Product Specification Sheet EPR 016270		ST321R-SF1SNF(CWH)	Issue: 11	Dated: 05-11-20 Dated: 05-11-20
Customer Tech Mar	ual 005665	Sinclair's commitment to product leadership may result in improvement or change to this product		

Copyright © Sinclair Technologies