



A Norsat Company in Norsat



ST321R-SF3SNF(CWH)

Mobile omni, 0 dBd, 20 MHz B.W., N-female, White, 450-470 MHz

Also referred as: EXCAL321RNF*3W

- · For use in both fixed and mobile installations
- · Proven performance in harsh environments

Minimum 30" x 30" ground plane is required.

Sinclair's radome-enclosed ST321R series of antennas is designed for a variety of mobile applications: railroad locomotives, taxis, police cars, emergency vehicles, buses and trucks.

Fire retardant radome is available.



Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com
Product Specification Sheet EPR 016270		ST321R-SF3SNF(CWH)	Issue: 11	Dated: 05-11-20 Dated: 05-11-20
Customer Tech Manual 005665		Sinclair's commitment to product leadership may result in improvement or change to this product		



UHF and Tetra Antennas ST321R Series

A Norsat Company	n	Norsat
------------------	---	--------


Frequency Range	MHz	450 to 470	
Bandwidth	MHz	20	
Connector		N-Female	
Gain (nominal)	dBd (dBi)	unity (2.1)	**
Input VSWR (max)	, ,	1.5:1	
Polarization		vertical	
Impedance	Ω	50	
Pattern		Omni-directional	*2
Average Input Power (max)	W	50	
Lightning protection		DC ground	
Mechanical Specifications Width	in (mm)	3 8 (97)	
Width	in (mm) in (mm)	3.8 (97) 3 (76)	
	in (mm) in (mm) in (mm)	3.8 (97) 3 (76) 11.8 (300)	
Width Length/ Height	in (mm)	3 (76) 11.8 (300)	
Width Length/ Height Length	in (mm)	3 (76)	
Width Length/ Height Length Radome material	in (mm)	3 (76) 11.8 (300) ABS (white)	
Width Length/ Height Length Radome material Mounting hardware	in (mm) in (mm)	3 (76) 11.8 (300) ABS (white) Supplied	

°F (°C)

Ordering Information
Specify operating frequency.

*1 : Similar to 1/4 wave monopole. *2 : Similar to 1/4 wave monopole.

Notes



Antennas

Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com
Product Specification Sheet		ST321R-SF3SNF(CWH)	Issue: 11	Dated: 05-11-20

-40 to +158 (-40 to +70)

Environmental Specifications

Temperature range