

## SUB-3803 Mobile omni antenna, 3 dBd gain, 380-400 MHz

- · High impact UV resistant ABS housing
- Stainless steel fittings
- · Stands up to severe environmental conditions

These antennas are fabricated from durable components and are designed to last. Rugged ABS housings are UV resistant and will not chalk, fade or crack. Fittings are constructed of stainless steel to inhibit rust and corrosion and are molded into the housing without the use of glue or fasteners to ensure a long lasting, reliable product, even in severe environments.

Many different mounts are available.

Optional shock spring available upon request.

## **Application Notes**

- Sinclair manufactures a wide range of mobile antennas. These products are very durable and reliable and can withstand the most severe environmental conditions. These antennas are suitable for public safety applications and other "mission critical" operations.
- Uses 1 1/8-18 (TAD/TAE) mounting.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 019013		SUB-3803	Issue: 1	Dated: 28-08-18 Dated: 28-08-18

Sinclair's commitment to product leadership may result in improvement or change to this product Copyright © Sinclair Technologies



A Norsat Company 🔟 Norsat

Frequency Range	MHz	380 to 400	
Bandwidth	MHz	20	
Gain (nominal)	dBd (dBi)	3 (5.1)	
Input VSWR (max)		1.5:1	
Polarization		vertical	
Impedance	Ω	50	
Pattern		Omni-directional	
Average Input Power (max)	W	100	

## **Mechanical Specifications**

Electrical Specifications

Length/ Height	in (mm)	14.88 (378)	
Weight	lbs (kg)	0.5 (0.23)	
Mounting configurations		upright	

°F (°C)

## **Environmental Specifications**

-40 to +140 (-40 to +60)

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world	
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165	
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com	
Product Specification Sheet EPR 019013		SUB-3803	Issue: 1	Dated: 28-08-18 Dated: 28-08-18	
Sinclair's commitment to product leadership may result in improvement or change to this product					

nclair's commitment to product leadership may result in improvement or change to this product Copyright © Sinclair Technologies