



A Norsat Company in Norsat



SUB-4062 Mobile omni antenna, 2 dBd, 406-430 MHz

- 5% Bandwidth (20 MHz typically)
- · Rugged ABS housings are UV resistant
- · Stainless steel fittings
- · 17-7PH Stainless Steel Whip material

These antennas are fabricated from durable components and are designed to last. Rugged ABS housings are UV resistant and will not chalk, fade or crack. Fittings are constructed of stainless steel to inhibit rust and corrosion and are molded into the housing without the use of glue or fasteners to ensure a long lasting, reliable product, even in severe environments.

Many different mounts are available.

Application Notes

• Sinclair manufactures a wide range of mobile antennas. These products are very durable and reliable and can withstand the most severe environmental conditions. These antennas are suitable for public safety applications and other "mission critical" operations.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Product Specification Sheet EPR 016628

SUB-4062

Issue: 3

Dated: 02-05-18

Dated: 16-09-13



Antennas
UHF and Tetra Antennas
SUB- UHF Series

A Norsat Company in Norsat

Frequency Range	MHz	406 to 430
% Bandwidth	%	5
Connector		1 1/8-18 (TAD/TAE)
Gain (nominal)	dBd (dBi)	2 (4.1)
Input VSWR (max)		1.5:1
Polarization		vertical
Pattern		Omni-directional
Average Input Power (max)	W	100

 Mechanical Specifications

 Length
 in (mm)
 15 (381)

 Weight
 lbs (kg)
 0.54 (0.25)

Environmental Specifications
Temperature range °F (°C) -40 to +140 (-40 to +60)

Ordering Information
Specify frequency of operation

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 016628		SUB-4062	Issue: 3	Dated: 02-05-18 Dated: 16-09-13