

Antennas UHF and Tetra Antennas SUB- UHF Series

<u>cı</u>	B-4	INA	30
აი	-Ч	FUO	১১

Mobile omni antenna, 3 dBd gain, 406-430 MHz

Also referred as: SUB-4063

· High impact UV resistant ABS housing

· Stainless steel fittings


· Stands up to severe environmental conditions

These antennas are fabricated from durable components and are designed to last. Rugged ABS housings are UV resistant and will not chalk, fade or crack. Fittings are constructed of stainless steel to inhibit rust and corrosion and are molded into the housing without the use of glue or fasteners to ensure a long lasting, reliable product, even in severe environments.

Many different mounts are available.

Application Notes

- Sinclair manufactures a wide range of mobile antennas. These products are very durable and reliable and can withstand the most severe environmental conditions. These antennas are suitable for public safety applications and other "mission critical" operations.
- Uses 1 1/8-18 (TAD/TAE) mounting.



www.sinctech.com

Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification She EPR 016634	neet	SUB-4063S	Issue: 1	Dated: 02-05-18 Dated: 20-05-15

Sinclair's commitment to product leadership may result in improvement or change to this product Copyright © Sinclair Technologies



Electrical Specifications			Notes
Frequency Range	MHz	406 to 430	*1 : 3.75%-15Mhz Typical
Bandwidth	MHz	15	*1
% Bandwidth	%	3.8	
Gain (nominal)	dBd (dBi)	3 (5.1)	
Input VSWR (max)		1.5:1	
Polarization		vertical	
Impedance	Ω	50	
Pattern		Omni-directional	
Average Input Power (max)	W	100	
Mechanical Specifications			
Length/ Height	in (mm)	16 (406)	Ordering Information
Weight	lbs (kg)	0.5 (0.23)	Ordering Information Specify frequency of operation and connector
Environmental Specifications			
Temperature range	°F (°C)	-40 to +140 (-40 to +60)	

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specificatior EPR 016634	n Sheet	SUB-4063S	Issue: 1	Dated: 02-05-18 Dated: 20-05-15
Sinclair's commitment to product leadership may result in improvement or change to this product				