

A Norsat Company 🔟 Norsat

SUB-4303S Mobile omni, 3 dBd, 5/8 wave, 430-470 MHz

Also referred as: SUB-4303

- Long-lasting, reliable service
 Do not require a ground plane and are ideal for installations on fiberglass vehicles (i.e. boats)
- Stainless Steel shock spring included.
- End fed, 5/8 wave

Fabricated from durable components this antenna is designed to last. Rugged ABS housings are UV resistant and will not chalk, fade or crack. Fittings are constructed of stainless steel to inhibit rust and corrosion and are molded into the housing without the use of glue or fasteners to ensure a long lasting, reliable product, even in severe applications.

Application Notes

 Available with shock spring Available with chrome or black chrome finish Length value is for the Whip at the lowest frequency





A Norsat Company n | Norsat

Antennas UHF and Tetra Antennas **SUB- UHF Series**

Electrical Specifications			Notes
Frequency Range	MHz	430 to 470	*1 : 3.5%-15Mhz Typical
Bandwidth	MHz	15	*1
% Bandwidth	%	3.5	
Gain (nominal)	dBd (dBi)	3 (5.1)	
Input VSWR (max)		1.5:1	
Polarization		vertical	
Impedance	Ω	50	
Pattern		Omni-directional	
Average Input Power (max)	W	100	
Mechanical Specifications			
Length/ Height	in (mm)	15.75 (400)	Ordering Information Specify frequency of operation and connector
Environmental Specifications			
Temperature range	°F (°C)	-40 to +140 (-40 to +60)	

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world	
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165	
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com	
Product Specification EPR 016635	n Sheet	SUB-4303S	Issue: 3	Dated: 02-05-18 Dated: 28-09-95	
Sinclair's commitment to product leadership may result in improvement or change to this product					