

SV227-SF2SNM Corner reflector directive, 7 dBd, 148-174 MHz

Also referred as: SRL227*2

- Folded dipole feed permits operation in severe conditions
- High power and heavy duty models available
- VSWR will not exceed 2.0:1 even with 0.5 in. of radial ice

Excellent broadband high gain corner reflector for use int 138-174 MHz frequency range. Its folded dipole feed permits operation under severe weather and ice conditions without significant change in pattern or VSWR. Even with 0.5 in of radial ice, the antenna VSWR will not exceed 2.0:1. Higher power and/or heavy-duty models are available.



www.sinctech.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Electrical Specifications


Frequency Range	MHz	148 to 174
Bandwidth	MHz	26
Connector		N-Male
Gain (nominal)	dBd (dBi)	7 (9.1)
Input VSWR (max)		1.5:1
Polarization		vertical or horizontal
Impedance	Ω	50
Pattern		Directional
Horizontal beamwidth (typ)	degrees	67
Vertical beamwidth (typ)	degrees	75
Average Power Input (max)	W	250
Lightning protection		DC ground
Front-to-back ratio (typ)	dB	30

Mechanical Specifications

Width	in (mm)	69.3 (1760)
Depth	in (mm)	49 (1245)
Length/ Height	in (mm)	48 (1219)
Radiating element material		aluminum
Weight	lbs (kg)	28.3 (12.85)
Weight iced (1/2" ice)	lbs (kg)	101 (45.85)
Mounting Hardware (Included)		Clamp004
Shipping dimensions	in (mm)	120x15x6 (3048x381x152)

Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)
Wind Loading Area (Flat Plate Equivalent)	ft ² (m ²)	5.3 (0.49)
Wind Loading Area (1/2" ice)	ft ² (m ²)	9.2 (0.85)
Rated wind velocity (no ice)	mph (km/h)	135 (217)
Rated wind velocity (1/2" radial ice)	mph (km/h)	95 (153)
Lateral thrust (100 mph No Ice)	lbs (N)	202 (898.5)



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com