

**SV402-SF2SNM** Corner reflector directive, 10 dBd, 896-960 MHz

Also referred as: SRL402\*2

- Compact, rugged, broadband corner reflector
- Resonant dipole is DC grounded and mounted into an aluminum reflector
- Nominal 10 dBd gain

This compact, rugged antenna is ideally suited to various requirements because of its low VSWR and uniform gain over its 100 MHz bandwidth. The antenna consists of a folded dipole, which is maintained at DC ground potential for lightning protection, and a specially designed aluminum reflector. The antenna provides a nominal 10 dBd gain.



www.sinctech.com

Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
<b>Telephone</b>	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
<b>E-mail</b>	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com

Product Specification Sheet  
EPR 015738  
Customer Tech Manual 006564

SV402-SF2SNM

Issue: 19

Dated: 01-04-20  
Dated: 31-03-20

### Electrical Specifications

Frequency Range	MHz	896 to 960
Connector		N-Male
Gain (nominal)	dBd (dBi)	10 (12.1)
Input VSWR (max)		1.5:1
Polarization		vertical or horizontal
Pattern		Directional
Horizontal beamwidth (typ)	degrees	30
Vertical beamwidth (typ)	degrees	52
Average Input Power (max)	W	100
Front-to-back ratio (Typ)	dB	30
Lightning protection		DC ground

### Mechanical Specifications


Width	in (mm)	48 (1219)
Depth	in (mm)	18 (457)
Length/ Height	in (mm)	24 (610)
Weight	lbs (kg)	23 (10.44)
Actual shipping weight	lbs (kg)	35 (15.89)
Shipping dimensions	in (mm)	50x21x34 (1270x533x864)

### Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)
Rated wind velocity (no ice)	mph (km/h)	100 (161)
Rated wind velocity (1/2" radial ice)	mph (km/h)	85 (137)
Lateral Thrust (100 mph No Ice)	lbs (N)	167 (742.8)

### Ordering Information

Clamps are included.  
The clamps support a mast pipe O.D. from 1.5 to 2.88 inches.



Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com