


SY2062-SF8SNM(C) Yagi directional, dual array, center mount, 12 dBd, 156-162 MHz

- Dual stacked six element Yagi for higher gain
- Does not include mounting pipe
- DC grounded for lightning protection
- Can be arranged horizontally or vertically stacked and horizontally or vertically polarized

The SY206 series of antennas consists of a six-element Yagi of outstanding durability and performance. All elements including the folded dipole are maintained at DC Ground potential for lightning protection. All elements on this antenna are attached to the boom with solid cast aluminum clamps. This highly versatile antenna is supplied as a standard mount Yagi, or, as an end-boom mounted unit. As with other Yagi's, this VHF antenna is available in multiple-unit arrays for added gain. Horizontally or vertically parallel kits of 'H' frames can readily be supplied to mount two or four Yagi's with a common feed.



Polarization	Stacking	Beamwidth	
		E-Plane	H-Plane
Vertical	Vertical	24	51
Vertical	Horizontal	44	36
Horizontal	Vertical	44	36
Horizontal	Horizontal	24	51

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Electrical Specifications

Frequency Range	MHz	156 to 162
Connector		N-Male
Gain (nominal)	dBd (dBi)	12 (14.1)
VSWR (max)		1.5:1
Polarization		vertical or horizontal
Pattern		Directional
Average Power Input (max)	W	300
Lightning protection		DC ground
Front-to-back ratio (typ)	dB	17

Notes


- *1 : Qty 2 included
- *2 : 2 antennas per box.

Mechanical Specifications

Width	in (mm)	5.5 (140)
Length/ Height	in (mm)	76 (1930)
Base pipe diameter	in (mm)	1.5 (38)
Radiating element material		aluminum
Weight	lbs (kg)	22.3 (10.12)
Weight iced (1/2" ice)	lbs (kg)	62.4 (28.33)
Mounting Hardware (Included)		Clamp001 *1
Actual shipping weight	lbs (kg)	34 (15.44)
Shipping dimensions	in (mm)	127x8x7 (3226x203x178) *2

Environmental Specifications

Temperature range	°F (°C)	-40 to +140 (-40 to +60)
Wind Loading Area (Flat Plate Equivalent)	ft² (m²)	2.71 (0.25)
Wind Loading Area (1/2" ice)	ft² (m²)	5.52 (0.51)
Rated wind velocity (no ice)	mph (km/h)	155 (250)
Rated wind velocity (1/2" radial ice)	mph (km/h)	95 (153)
Lateral Thrust (100 mph No Ice)	lbs (N)	66 (293.6)



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com