

A Norsat Company in Norsat

Transmitter Combiners Low Band, Aviation, and VHF Transmitter Combiners TC2 Series

TC2112 Combiner, hybrid-ferrite, 2 channels, single stage isolators, 132-174 MHz

- · Supports extremely close frequency spacings
- 50 dB of Tx to Tx isolation
- · Permit combining two 132-174 MHz transmitters into one antenna

These transmitter combiners can be used in those systems requiring extremely close frequency separations. They utilize isolators, hybrids and terminations in a compact mechanical configuration allowing a 2-channel transmitter combiner to be mounted in only 3.5 inches of rack space. Standard configurations permit combining up to four transmitters into one antenna. For more than four transmitter, higher isolation, VSWR and power monitoring options, or unusual power requirements, consult your Sinclair applications engineers.

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification	n Sheet	TC2112	Issue: 3	Dated: 20-11-17

Product Specification Sheet EPR 15969

Issue: 3 Dated: 27-09-13



Transmitter Combiners Low Band, Aviation, and VHF Transmitter Combiners TC2 Series

A Norsat Company Norsat

Electrical Specifications			
Frequency Range	MHz	132 to 174	
Number of channels		2	
Input Connectors		N-Female	
Output Connectors		N-Female	
Input VSWR (max)		1.25:1	
Insertion Loss (max) Tx to Ant	dB	3.9	
Power (Per Channel)	W	125	
Frequency separation (max)	MHz	3	
Frequency separation (min)	MHz	0	
Isolation Tx to Tx	dB	50	
Isolation antenna to Tx	dB	28	

Width	in (mm)	19 (483)
Depth	in (mm)	15.63 (397)
Length/ Height	in (mm)	3.5 (89)
Weight	lbs (kg)	11.6 (5.27)
Actual shipping weight	lbs (kg)	20 (9.08)
Shipping dimensions	in (mm)	19x26x7 (483x660x178)

Shipping dimensions	III (IIIIII)	19X20X1 (403X00UX110)	
Environmental Specifications			
Environmental opcomoations			
Temperature range	°F (°C)	-22 to +140 (-30 to +60)	

Ordering Information
Specify one Tx frequency per channel when ordering.

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		TC2112	Issue: 3	Dated: 20-11-17