EPR 016832

Customer Tech Manual 006352



Transmitter Combiners
UHF and Tetra Transmitter Combiners
TC3 Series

A Norsat Company in | Norsat International Inc.

TC3113 Hybrid-Ferrite Transmitter Combiner, 3 channel, single stage isolators, 400-512 MHz

- Supports extremely close frequency spacings
- · Permit combining two or four 400-512 MHz transmitters into one antenna
- · Compact 19 inch rack mount
- · Ships in two boxes

These transmitter combiners can be used in those systems requiring extremely close frequency separations. They utilize Sinclair manufactured isolators, hybrid couplers, harmonic filters and terminations in a compact mechanical configuration. Standard configurations permit combining up to four transmitters into one antenna. For more than four transmitters, higher isolation, VSWR and power monitoring options, or unusual power requirements, consult Sinclair systems engineers.



2 channel model shown

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification	n Sheet	TC3113	Issue: 4	Dated: 24-11-17

Dated: 24-11-17



## Transmitter Combiners UHF and Tetra Transmitter Combiners TC3 Series

A Norsat Company in Norsat

Electrical Specifications			
Frequency Range	MHz	400 to 512	
Number of channels		3	
Input Connectors		N-Female	
Output Connectors		N-Female	
Input VSWR (max)		1.25:1	
Insertion Loss (max) Tx to Ant	dB	5.6	
Maximum Input Power (per channel)	W	125	
Frequency separation (max)	MHz	9	
Frequency separation (min)	MHz	0	
Isolation Tx to Tx	dB	60	
Isolation antenna to Tx	dB	30	

Notes \*1 : 2 packages

Mechanical Specifications			
Width	in (mm)	19 (483)	
Depth	in (mm)	15.63 (397)	
Length/ Height	in (mm)	7 (178)	
Weight	lbs (kg)	22 (9.99)	
Actual shipping weight	lbs (kg)	30 (13.62)	
Shipping dimensions	in (mm)	26x19x7 (660x483x178)	*1

**Ordering Information**Specify one Tx frequency per channel when ordering.

<b>Environmental Specifications</b>			
Temperature range	°F (°C)	-22 to +140 (-30 to +60)	

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 016832		TC3113	Issue: 4	Dated: 24-11-17 Dated: 24-11-17
Customer Tech Manual 006352		Sinclair's commitment to product leadership may result in i	improvement or change to this product	