

Transmitter Combiners
700 -1000 MHz Transmitter Combiners
TC4 Series

TC4214 Combiner, hybrid-ferrite, single stage isolator, 4 channels, 806-960 MHz

- Supports extremely close frequency spacings (0-10 MHz separation)
- · Connects four 125W transmitters to one antenna
- · Dual stage isolators

These transmitter combiners can be used in those systems requiring extremely close frequency separations. They utilize Sinclair manufactured isolators, hybrids, and terminations in a compact mechanical configuration allowing a 4-channel transmitter combiner to be mounted in only 10.5 inches of rack space.

| Region | United States | Europe, Middle East and Africa | Caribbean and Latin America | Canada and rest of the world |
|-----------------------|-----------------------|--------------------------------------|--------------------------------|--|
| Telephone | USA: 1 800 263 3275 | International: +44 (0) 1487 84 28 19 | International: +1 905 726 7676 | Canada: 1 800 263 3275 International: +1 905 727 0165 |
| E-mail | salesusa@sinctech.com | salesuk@sinctech.com | salesla@sinctech.com | salescan@sinctech.com |
| Product Specification | n Sheet | TC4214 | leane. 6 | Dated: 20-11-17 |

Dated: 28-05-15



Transmitter Combiners 700 -1000 MHz Transmitter Combiners TC4 Series

A Norsat Company in Norsat International Inc.

| Electrical Specifications | | | |
|-----------------------------------|-----|------------|----|
| Frequency Range | MHz | 806 to 960 | |
| Number of channels | | 4 | *1 |
| Input Connectors | | N-Female | |
| Output Connectors | | N-Female | |
| Input VSWR (max) | | 1.25:1 | |
| Insertion loss (typ) Tx to Ant | dB | 7.4 | |
| Maximum Input Power (per channel) | W | 125 | |
| Frequency separation (max) | MHz | 10 | |
| Frequency separation (min) | MHz | 0 | |
| Isolation Tx to Tx | dB | 80 | |
| Isolation antenna to Tx | dB | 53 | |

Notes

*1 : Qty 3- 2U trays *2 : 3 boxes

| Width | in (mm) | 19 (483) | |
|---------------------|----------|-----------------------|----|
| Depth | in (mm) | 15.63 (397) | |
| Length/ Height | in (mm) | 10.5 (267) | |
| Weight | lbs (kg) | 29.9 (13.57) | |
| Shipping dimensions | in (mm) | 19x26x7 (483x660x178) | ** |

Ordering Information
Specify the four Tx channel frequencies when ordering.

| Environmental Specifications | | | | |
|------------------------------|---------|--------------------------|--|--|
| Temperature range | °F (°C) | -22 to +140 (-30 to +60) | | |

| Region | United States | Europe, Middle East and Africa | Caribbean and Latin America | Canada and rest of the world |
|---|-----------------------|---|--------------------------------|--|
| Telephone | USA: 1 800 263 3275 | International: +44 (0) 1487 84 28 19 | International: +1 905 726 7676 | Canada: 1 800 263 3275 International: +1 905 727 0165 |
| E-mail | salesusa@sinctech.com | salesuk@sinctech.com | salesla@sinctech.com | salescan@sinctech.com |
| Product Specification Sheet EPR 015975 | | TC4214 | Issue: 6 | Dated: 20-11-17 Dated: 28-05-15 |
| Customer Tech Manual 005796 | | Sinclair's commitment to product leadership may result in improvement or change to this product | | |