


TCC3132-(X) Combiner, hybrid-ferrite, compact, 2 CH, single stage isolator, 350-512 MHz

- Connect two 60W transmitters to one antenna
- · Single stage isolators
- 1U high compact housing

Sinclair's new TCC series of hybrid ferrite transmitter combiners allow up to four 60 Watt transmitters to be combined onto one antenna. With single stage isolators, the units provide 45 dB of Tx to Tx isolation. With dual stage isolators, the Tx to Tx isolation is 70 dB. The minimum frequency separation is 0 MHz. The frequencies can be changed without having to re-tune the combiner.

When ordering please see below chart for detailed part# and frequency configuration.



Part#	Frequency (MHz)	Frequency Separation (MHz) Min-Max
TCC3132-1	350-385	0-35
TCC3132-2	380-415	0-35
TCC3132-3	405-440	0-35
TCC3132-4	430-470	0-40
TCC3132-5	459-512	0-53

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 018454-1 Customer Tech Manual 006114		TCC3132-(X)	Issue: 2	Dated: 24-05-19 Dated: 23-05-19



A Norsat Company 🔟 Norsat

Transmitter Combiners UHF and Tetra Transmitter Combiners TCC3 Series

Electrical Specifications			
Frequency Range	MHz	350 to 512	*1
Number of channels		2	
Input Connectors		N-Female	
Output Connectors		N-Female	
Input VSWR (max)	1.3:1		
Output VSWR	1.5:1		
Insertion Loss (typ) Tx to Ant	dB	4.1	*2
Power (Per Channel)	W	60	
Isolation Tx to Tx	dB	45	
Isolation antenna to Tx	dB	28	

Notes *1 : See details in the previous page. *2 : ±0.4 dB

Mechanical Specifications

Width	in (mm)	19 (483)
Depth	in (mm)	10 (254)
Length/ Height	in (mm)	1.75 (44)
Weight	lbs (kg)	10 (4.54)
Shipping dimensions	in (mm)	25.5x18.75x6.5 (648x476x165)

Environmental Specifications

Temperature range	°F (°C)	-22 to +140 (-30 to +60)		

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 018454-1 Customer Tech Manual 006114				Dated: 24-05-19 Dated: 23-05-19
		Sinclair's commitment to product leadership may result in improvement or change to this product		

air's commitment to product leadership may result in improvement or change to this produ Copyright © Sinclair Technologies