


Transmitter Combiners
UHF and Tetra Transmitter Combiners
TJ3x1y-R-z Series

TJ3112-R-5 Cavity-Ferrite Transmitter Combiner, 2 Channels, 7" Cavities, 459-512 MHz

- · Low loss broad band single stage isolators
- · Allows for minimum Tx-Tx spacings of 200 KHz
- Expandable for more channels
- · Uses high 'Q' 1/4 wave bandpass cavity filters

Sinclair's 'TJ3x1y-R-z' series cavity ferrite transmitter combiners are available in 2 to 5 channel configurations for use in systems from 330-512 MHz. Each channel on these combiners includes a low-loss, broad band single or dual-stage isolator and High 'Q' 1/4 wave bandpass cavity filter suitable for close channel separations, typically 200 KHz.

The 'TJ3x1y-R-z' series combiners can be expanded to 20 channels. For expansion please contact your Sinclair Sales Representative or Customer Service Representative.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com

Sinclair's commitment to product leadership may result in improvement or change to this product

Copyright © Sinclair Technologies

Temperature range



Transmitter Combiners UHF and Tetra Transmitter Combiners TJ3x1y-R-z Series

A Norsat Company in Norsat

Frequency Range	MHz	459 to 512	
Number of channels	WIIIZ	2	
Input Connectors		N-Female	
Output Connectors		N-Female	
Input VSWR (max)		1.25:1	
Output VSWR		2:1	
Insertion Loss (typ) Tx to Ant	dB	2.9	*
Maximum Input Power (per channel)	W	125	
Frequency separation (min)	MHz	0.2	
Isolation Tx to Tx	dB	35	
Isolation antenna to Tx	dB	25	
Cavity electrical length		1/4	
			
Mechanical Specifications Width	in (mm)	19 (483)	
Depth	in (mm)	7 (178)	
	in (mm)	15.3 (389)	
Lanath/Haiaht	111 (111111)	` ,	
	lhe (ka)		
Length/ Height Weight Actual shipping weight	lbs (kg) lbs (kg)	20 (9.08) 28 (12.71)	
Length/ Height Weight	lbs (kg)	20 (9.08)	


°F (°C)

Notes

*1: @ 250 kHz Tx-Tx spacing

Ordering Information

Specify one Tx frequency per channel at time of order.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 018651		TJ3112-R-5	Issue: 1	Dated: 22-08-19 Dated: 24-11-11

-22 to +140 (-30 to +60)