

Transmitter Combiners UHF and Tetra Transmitter Combiners TJ3 Series

### TJ3113 Cavity-ferrite Tx combiner, 3 channels, single stage isolator, 406-512 MHz

- Three channel cavity-ferrite combiner in compact configuration, 406-512 MHz.
- Single low-loss isolator
- High Q bandpass cavity filters

Sinclair's 'TJ3' series cavity ferrite transmitter combiners are available in 2 to 8 channel configurations for use in systems from 406-512 MHz. Each channel on these combiners includes a low-loss single or dual-stage isolator and Sinclair-developed High 'Q' bandpass cavity filter. They utilize very high 'Q' one-quarter wavelength cavities and is especially suitable for close channel separations, typically 200 kHz.



All models are 19-inch rack mountable.

The 'TJ3' series combiner is easily expanded to 20 channels upon request and is the building block used in many Sinclair combining systems. Common electrical specifications are shown below.

To select the combiner ideally suited to your application, please consult your Sinclair customer service representative.

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 017751		TJ3113	Issue: 40	Dated: 13-03-18 Dated: 22-05-02
EPR 017751				Dated: 22-05-02



## A Norsat Company 🔟 Norsat

# Transmitter Combiners UHF and Tetra Transmitter Combiners TJ3 Series


Electrical Specifications			Notes
Frequency Range	MHz	406 to 512	*1 : Qty 3 boxes
Number of channels		3	
Input Connectors		N-Female	
Output Connectors		N-Female	
Input VSWR (max)		1.25:1	
Output VSWR		2:1	
Average Input Power (max)	W	125	
Frequency separation (min)	MHz	0.2	
Isolation Tx to Tx	dB	35	
Isolation antenna to Tx	dB	25	

### **Mechanical Specifications**

Width	in (mm)	19 (483)	
Depth	in (mm)	15.3 (389)	
Length/ Height	in (mm)	12.25 (311)	
Weight	lbs (kg)	17 (7.72)	
Actual shipping weight	lbs (kg)	60 (27.24)	
Shipping dimensions	in (mm)	26x19x7 (660x483x178)	*1

### **Environmental Specifications**

Temperature range	°F (°C)	-22 to +140 (-30 to +60)	



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 017751		TJ3113	Issue: 40	Dated: 13-03-18 Dated: 22-05-02
Cincleide commitment to product leadership may recult in improvement or change to this product				

Sinclair's commitment to product leadership may result in improvement or change to this product Copyright © Sinclair Technologies