


Transmitter Combiners
UHF and Tetra Transmitter Combiners
TJ3x1y-R-z Series

A Norsat Company in Norsat International Inc.

TJ3214-R-E6383 Cavity-Ferrite Transmitter Combiner, 4 Channels, 7" Cavities, 361-366 MHz

- · Low loss broad band dual stage isolators
- · Allows for minimum Tx-Tx spacings of 250 KHz
- · Expandable for more channels
- · Uses high 'Q' 1/4 wave bandpass cavity filters

Sinclair's 'TJ3x1y-R-z' series cavity ferrite transmitter combiners are available in 2 to 8 channel configurations for use in systems in UHF & Tetra. Each channel on these combiners includes a low-loss, broad band single or dual-stage isolator and High 'Q' 1/4 wave bandpass cavity filter suitable for close channel separations, typically 250 KHz.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		TJ3214-R-E6383	Issue: 0	Dated: 11-09-17



## Transmitter Combiners UHF and Tetra Transmitter Combiners TJ3x1y-R-z Series

A Norsat Company in Norsat

Clastriani Chasifications

Electrical Specifications			
Frequency Range	MHz	361 to 366	
Number of channels		4	
Input Connectors		N-Female	
Output Connectors		N-Female	
Input VSWR (max)		1.25:1	
Output VSWR		2:1	
Insertion loss (typ) Tx to Ant	dB	3.5	*1
Maximum Input Power (per channel)	W	125	
Frequency separation (min)	MHz	0.25	
Isolation Tx to Tx	dB	70	
Isolation antenna to Tx	dB	60	
Cavity electrical length		1/4	
Machanical Specifications			
Mechanical Specifications Width	in (mm)	19 (483)	
Depth	in (mm)	14.8 (376)	
Length/ Height	in (mm)	20 (508)	
For instance to LO and First in a			
Environmental Specifications	0F (0A)	00 t- 440 / 20 t- 60)	
Temperature range	°F (°C)	-22 to +140 (-30 to +60)	

## Notes \*1 ⋅ @ 250

\*1: @ 250 kHz Tx-Tx spacing

## Ordering Information

Specify one Tx frequency per channel at time of order.

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		TJ3214-R-E6383	Issue: 0	Dated: 11-09-17