


**Transmitter Combiners UHF and Tetra Transmitter Combiners** TJ3x1y-R-z Series

TJ3215-R-1 Cavity-Ferrite Transmitter Combiner, 5 Channels, 7" Cavities, 330-355 MHz

- · Low loss broad band dual stage isolators
- · Allows for minimum Tx-Tx spacings of 250 KHz
- Expandable for more channels
- · Uses high 'Q' 1/4 wave bandpass cavity filters

Sinclair's 'TJ3x1y-R-z' series cavity ferrite transmitter combiners are available in 2 to 5 channel configurations for use in systems from 330-512 MHz. Each channel on these combiners includes a low-loss, broad band single or dual-stage isolator and High 'Q' 1/4 wave bandpass cavity filter suitable for close channel separations, typically 250 KHz.

The 'TJ3x1y-R-z' series combiners can be expanded to 20 channels. For expansion please contact your Sinclair Sales Representative or Customer Service Representative.



Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification	n Sheet	TJ3215-R-1	Issue: 1	Dated: 11-09-17

**Product Specification Sheet** EPR 018935 Customer Tech Manual 006703 TJ3215-R-1

Dated: 02-11-16



## **Transmitter Combiners UHF and Tetra Transmitter Combiners** TJ3x1y-R-z Series

A Norsat Company in Norsat

Clastriani Canadinations

Electrical Specifications			
Frequency Range	MHz	330 to 355	
Number of channels		5	
Input Connectors		N-Female	
Output Connectors		N-Female	
Input VSWR (max)		1.25:1	
Output VSWR		2:1	
Insertion Loss (typ) Tx to Ant	dB	3.8	*1
Maximum Input Power (per channel)	W	125	
Frequency separation (min)	MHz	0.25	
Isolation Tx to Tx	dB	60	
Isolation antenna to Tx	dB	50	
Cavity electrical length		1/4	
Mechanical Specifications			
Width	in (mm)	19 (483)	
Depth	in (mm)	21.3 (541)	
Length/ Height	in (mm)	21.2 (538)	
Shipping dimensions	in (mm)	22x22x43 (559x559x1092)	
Environmental Specifications			
Temperature range	°F (°C)	-22 to +140 (-30 to +60)	

## \*1: @ 250 kHz Tx-Tx spacing

Notes

## **Ordering Information**

Specify one Tx frequency per channel at time of order.

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet EPR 018935		TJ3215-R-1	Issue: 1	Dated: 11-09-17 Dated: 02-11-16

EPR 018935 Customer Tech Manual 006703