

Vinyl-Tec 2000 Adhesive

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 14/01/2019 Date of issue: 14/01/2019

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Vinyl-Tec 2000 Adhesive

1.2. Intended Use of the Product: Not available

1.3. Name, Address, and Telephone of the Responsible Party

Company

North Water Holdings Ltd.

110-2331 Alberta Street

Vancouver, BC V5Y-4A7

1-800-567-9283

604-264-0824

www.northwater.com

1.4. Emergency Telephone Number

Emergency Number : CANUTEC 613-996-6666 / CHEMTREC 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US classification

Flam. Liq. 2 H225

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Repr. 2 H361

STOT SE 3 H336

STOT RE 2 H373

Aquatic Acute 3 H402

Full text of H-phrases: see section 16

2.2. Label Elements

GHS-US Labeling



GHS02



GHS07



GHS08

Hazard Pictograms (GHS-US) :

Signal Word (GHS-US) :

Hazard Statements (GHS-US) :

- : Danger
- : H225 - Highly flammable liquid and vapor.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H402 - Harmful to aquatic life.

Precautionary Statements (GHS-US) :

- : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapors, mist, spray.

Vinyl-Tec 2000 Adhesive

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CENTER, a doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P370+P378 - In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, alcohol resistant foam to extinguish.
P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.

2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US) No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

3.2. Mixture

Name	Product Identifier	% (w/w)
Acetone	(CAS No) 67-64-1	60 – 100
Toluene	(CAS No) 108-88-3	15 - 40

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye irritation. Causes skin irritation. May cause drowsiness and dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

Vinyl-Tec 2000 Adhesive

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Highly flammable liquid and vapor. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Thermal decomposition generates: Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not breathe vapor, mist or spray. Avoid all contact with skin, eyes, or clothing.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Vinyl-Tec 2000 Adhesive

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Isocyanates.

7.3. Specific End Use(s)

Not available

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Acetone (67-64-1)		
Mexico	OEL TWA (mg/m ³)	2400 mg/m ³
Mexico	OEL TWA (ppm)	1000 ppm
Mexico	OEL STEL (mg/m ³)	3000 mg/m ³
Mexico	OEL STEL (ppm)	1260 ppm
USA ACGIH	ACGIH TWA (ppm)	250 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	Biological Exposure Indices (BEI)	25 mg/l (Medium: urine - Time: end of shift - Parameter: Acetone (nonspecific))
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	590 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
USA IDLH	US IDLH (ppm)	2500 ppm (10% LEL)
Alberta	OEL STEL (mg/m ³)	1800 mg/m ³
Alberta	OEL STEL (ppm)	750 ppm
Alberta	OEL TWA (mg/m ³)	1200 mg/m ³
Alberta	OEL TWA (ppm)	500 ppm
British Columbia	OEL STEL (ppm)	500 ppm
British Columbia	OEL TWA (ppm)	250 ppm
Manitoba	OEL STEL (ppm)	500 ppm
Manitoba	OEL TWA (ppm)	250 ppm
New Brunswick	OEL STEL (mg/m ³)	1782 mg/m ³
New Brunswick	OEL STEL (ppm)	750 ppm
New Brunswick	OEL TWA (mg/m ³)	1188 mg/m ³
New Brunswick	OEL TWA (ppm)	500 ppm
Newfoundland & Labrador	OEL STEL (ppm)	500 ppm
Newfoundland & Labrador	OEL TWA (ppm)	250 ppm
Nova Scotia	OEL STEL (ppm)	500 ppm
Nova Scotia	OEL TWA (ppm)	250 ppm
Nunavut	OEL STEL (mg/m ³)	2970 mg/m ³
Nunavut	OEL STEL (ppm)	1250 ppm
Nunavut	OEL TWA (mg/m ³)	2370 mg/m ³
Nunavut	OEL TWA (ppm)	1000 ppm
Northwest Territories	OEL STEL (ppm)	750 ppm
Northwest Territories	OEL TWA (ppm)	500 ppm
Ontario	OEL STEL (ppm)	750 ppm
Ontario	OEL TWA (ppm)	500 ppm

Vinyl-Tec 2000 Adhesive

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Prince Edward Island	OEL STEL (ppm)	500 ppm
Prince Edward Island	OEL TWA (ppm)	250 ppm
Québec	VECD (mg/m ³)	2380 mg/m ³
Québec	VECD (ppm)	1000 ppm
Québec	VEMP (mg/m ³)	1190 mg/m ³
Québec	VEMP (ppm)	500 ppm
Saskatchewan	OEL STEL (ppm)	750 ppm
Saskatchewan	OEL TWA (ppm)	500 ppm
Yukon	OEL STEL (mg/m ³)	3000 mg/m ³
Yukon	OEL STEL (ppm)	1250 ppm
Yukon	OEL TWA (mg/m ³)	2400 mg/m ³
Yukon	OEL TWA (ppm)	1000 ppm
Toluene (108-88-3)		
Mexico	OEL TWA (mg/m ³)	188 mg/m ³
Mexico	OEL TWA (ppm)	50 ppm
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	Biological Exposure Indices (BEI)	0.02 mg/l (Medium: blood - Time: prior to last shift of workweek - Parameter: Toluene) 0.03 mg/l (Medium: urine - Time: end of shift - Parameter: Toluene) 0.3 mg/g Kreatinin (Medium: urine - Time: end of shift - Parameter: o-Cresol with hydrolysis (background))
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	375 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	560 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
USA IDLH	US IDLH (ppm)	500 ppm
Alberta	OEL TWA (mg/m ³)	188 mg/m ³
Alberta	OEL TWA (ppm)	50 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL TWA (mg/m ³)	188 mg/m ³
New Brunswick	OEL TWA (ppm)	50 ppm
Newfoundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (mg/m ³)	560 mg/m ³
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (mg/m ³)	375 mg/m ³
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (ppm)	60 ppm
Northwest Territories	OEL TWA (ppm)	50 ppm
Ontario	OEL TWA (ppm)	20 ppm
Prince Edward Island	OEL TWA (ppm)	20 ppm
Québec	VEMP (mg/m ³)	188 mg/m ³
Québec	VEMP (ppm)	50 ppm
Saskatchewan	OEL STEL (ppm)	60 ppm
Saskatchewan	OEL TWA (ppm)	50 ppm
Yukon	OEL STEL (mg/m ³)	560 mg/m ³

Vinyl-Tec 2000 Adhesive

Safety Data Sheet


According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m ³)	375 mg/m ³
Yukon	OEL TWA (ppm)	100 ppm

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

Hand Protection: Wear protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Translucent off-white
Odor	: Mild
Odor Threshold	: Not available
pH	: Not applicable
Evaporation Rate	: 11.6, based on Acetone [Ref Std: <i>n</i> -Butyl acetate = 1.0]
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 53 - 78 °C (127.4 - 172.4 °F)
Flash Point	: < -30 °C (-22 °F) (Tag Closed Cup)
Auto-ignition Temperature	: >465 °C (869 °F)
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: 1.3 %
Upper Flammable Limit	: 13.0 %
Vapor Pressure	: <=184 mm Hg @ 20 °C (68 °F)
Relative Vapor Density at 20 °C	: >= 2.0 [Ref Std: Air = 1.0]
Relative Density	: 0.86 g/mL
Specific Gravity	: 0.86 @ 20 °C (68 °F)
Solubility	: Not soluble in water
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: 6,000 – 7,000 centipoise @ 20 °C (68 °F)
Solids Content	: 18 ± 2%
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Yes, in certain circumstances product can ignite due to static discharge.
VOC Content (SCAQMD Rule 1168)	: 507 g/L (4.23 lbs/gal)
VHAP Content	: 1.0 lb/lb solids

Vinyl-Tec 2000 Adhesive

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.
- 10.2. **Chemical Stability:** Extremely flammable liquid and vapor. May form flammable or explosive vapor-air mixture.
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- 10.5. **Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Isocyanates.
- 10.6. **Hazardous Decomposition Products:** Thermal decomposition generates: Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

- Acute Toxicity:** Not classified
- LD50 and LC50 Data:** Not available
- Skin Corrosion/Irritation:** Causes skin irritation.
- Serious Eye Damage/Irritation:** Causes serious eye irritation.
- Respiratory or Skin Sensitization:** Not classified
- Germ Cell Mutagenicity:** Not classified
- Teratogenicity:** Not classified
- Carcinogenicity:** Not classified
- Specific Target Organ Toxicity (Repeated Exposure):** May cause damage to organs through prolonged or repeated exposure.
- Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.
- Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness.
- Aspiration Hazard:** Not classified
- Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.
- Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis.
- Symptoms/Injuries After Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.
- Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.
- Chronic Symptoms:** Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Acetone (67-64-1)	
LD50 Oral Rat	5800 mg/kg
LD50 Dermal Rabbit	15688 mg/kg
LC50 Inhalation Rat	44 g/m ³
LC50 Inhalation Rat	75.8 mg/l/4h
Toluene (108-88-3)	
LD50 Oral Rat	5580 mg/kg
LD50 Dermal Rabbit	12000 mg/kg
LC50 Inhalation Rat	12.5 mg/l/4h
LC50 Inhalation Rat	25.7 mg/l/4h
Acetone (67-64-1)	
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.
Toluene (108-88-3)	
IARC Group	3

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Harmful to aquatic life.

Vinyl-Tec 2000 Adhesive

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Acetone (67-64-1)	
LC50 Fish 1	4144.846 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	1679.66 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	6210 (6210 - 8120) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	12600 (12600 - 12700) mg/l (Exposure time: 48 h - Species: Daphnia magna)
Toluene (108-88-3)	
LC50 Fish 1	15.22 (15.22 - 19.05) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 (5.46 - 9.83) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC chronic crustacea	0.74 mg/l (Ceriodaphnia dubia)

12.2. Persistence and Degradability

Vinyl-Tec 2000	
Persistence and Degradability	Not established.
Acetone (67-64-1)	
Persistence and Degradability	Readily biodegradable in water.

12.3. Bioaccumulative Potential

Vinyl-Tec 2000	
Bioaccumulative Potential	Not established.
Acetone (67-64-1)	
BCF Fish 1	0.69
Log Pow	-0.24
Log Kow	-0.24
Toluene (108-88-3)	
Log Pow	2.65

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology – Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT

Proper Shipping Name : ADHESIVES
Hazard Class : 3
Identification Number : UN1133
Label Codes : 3
Packing Group : II
ERG Number : 127



14.2. In Accordance with IMDG

Proper Shipping Name : ADHESIVES
Hazard Class : 3
Identification Number : UN1133
Packing Group : II
Label Codes : 3

Vinyl-Tec 2000 Adhesive

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

EmS-No. (Fire) : F-E
 EmS-No. (Spillage) : S-E



14.3. In Accordance with IATA

Proper Shipping Name : ADHESIVES
 Packing Group : II
 Identification Number : UN1133
 Hazard Class : 3
 Label Codes : 3
 ERG Code (IATA) : 3H



14.4. In Accordance with TDG

Proper Shipping Name : ADHESIVES
 Packing Group : II
 Hazard Class : 3
 Identification Number : UN1133
 Label Codes : 3



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Vinyl-Tec 2000 Adhesive	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
Acetone (67-64-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Toluene (108-88-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
RQ (Reportable Quantity, Section 304 of EPA's List of Lists):	1000 lb
SARA Section 313 - Emission Reporting	1.0 %

15.2. US State Regulations

Toluene (108-88-3)	
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.
Acetone (67-64-1)	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	
Toluene (108-88-3)	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	


15.3. Canadian Regulations

Vinyl-Tec 2000 Adhesive

Vinyl-Tec 2000 Adhesive

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
	
Acetone (67-64-1)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Toluene (108-88-3)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 15/01/2019
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

H225	Highly flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life

Party Responsible for the Preparation of This Document

North Water Holdings Ltd.
110 – 2331 Alberta Street
Vancouver, BC V5Y-4A7
T: 604-264-0827

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS