

Product Name:	Bluelab Combo Meter
Product Code:	METCOM
UPC Code:	9421024920036
Country of Origin:	New Zealand
Tariff Code:	9027.80
Shipping Quantity:	Sold as singular unit
Packaging Information:	
Packaged Weight:	0.48 kg / 1.06 lb
Packaged Length:	180 mm / 7.086 in
Packaged Width:	110 mm / 4.33 in
Packaged Height:	83 mm / 3.267 in

Sales Description:

NOTE: this copy can be used in brochures, catalogues or online

pH, conductivity and temperature in one portable meter - simple

A convenient and portable solution pH, conductivity, and temperature meter all in one.

Easy to read screen and push button operation, choose your preferred parameter to display.

Portable with no external power supply required, this meter can be used anytime and anywhere to help manage your plant's daily nutrient requirements.

Team with Bluelab® solutions and the convenient Bluelab® Carry Case.

Probe cable length: 2 meters / 6.5 feet

Register your product here: <http://bluelab.com/product-registration>

Features:

- Replaceable double junction pH probe included
- Shows conductivity scales CF, EC, PPM 500 & PPM 700 at the touch of a button
- Lightweight and portable
- Large easy to read, backlit LCD display
- No calibration required for conductivity and temperature (factory calibrated)
- Simple two point pH calibration process with 30 day calibration indicator
- Over range and under range indicators
- Low battery indicator
- 2x AAA alkaline batteries included
- Auto off function

Product Guarantee:

Five year free repair or replacement guarantee.
* Six months for pH Probe.


Product Image:

Product images available for Screen or Web use:

- Bluelab-ComboMeter-MR-flat-RGB.jpg
- Bluelab-ComboMeter-WEB.jpg
- Bluelab-ComboMeter-Web-sml.jpg

Product images available for PRINT:

Note: these images are high resolution in CMYK.

- Bluelab-ComboMeter-MR-flat-CMYK.tif

Technical Specifications:

Measurement Range:	0.0 – 14.0 pH, 0.0 – 9.9 EC, 99 CF 0 – 4950 ppm 500 (EC x 500) 0 – 6930 ppm 700 (EC x 700) 0 – 50 °C / 32 – 122 F
Resolution:	0.1 pH, 0.1 EC, 1 CF 10 ppm 500, 10 ppm 700 1 °C / 1 F
Accuracy at 2.77 EC and 25°C / 77°F:	± 0.1 pH, ± 0.1 EC, ± 1 CF, ± 50 ppm 500, ± 70 ppm 700 ± 1 °C / ± 2 F
Automatic Temperature Compensation:	Yes
Operating Environment:	0 – 50 °C / 32 – 122 F
Calibration:	Not required for conductivity. pH requires two point, pH 7.0 & pH 4.0 or pH 10.0 calibration
Power Source:	2 x AAA alkaline batteries
User Manual Languages Available:	English
Certifications:	CE and FCC