

Quest 165 and 225 Dual



High-Efficiency Dehumidifiers

1.877.420.1330
www.QuestClimate.com



PATENTS:
D570,988
8,069,681



Specifications @ 80°F and 60% RH:				
Unit:	4037410 165 Dual		4035400 225 Dual	
Blower: (Tested with duct collars on)	391 CFM @ 0.0" WG 363 CFM @ 0.2" WG 337 CFM @ 0.4" WG		526 CFM @ 0.0" WG 495 CFM @ 0.2" WG 458 CFM @ 0.4" WG	
Power (Watts):	860		1500	
Supply voltage:	220-240 VAC - 1 Phase - 60 Hz.		220-240 VAC - 1 Phase - 60 Hz.	
Current Draw (Amps):	3.6		6.9	
Energy Factor:	3.7 L/kWh		2.9 L/kWh	
Operating Temp:	56°F - 95°F		56°F - 95°F	
Water Removal (Pints/Day):	165		225	
Efficiency (Pints/kWh):	7.8		6.1	
Air Filter (MERV-11 Nominal):	Size: 16" x 20" x 2"		Size: 16" x 20" x 2"	
Power Cord: 10' 14/3 SJTW	NEMA 6-15P 		NEMA 6-15P 	
Drain Connection:	3/4" Threaded NPT		3/4" Threaded NPT	
Refrigerant Type: Refrigerant Amount:	R410A 2lb. 0oz.		R410A 2lb. 0oz.	
Dimensions:	Unit	Shipping	Unit	Shipping
Width:	20.25"	25"	20.25"	25"
Height:	21.75"	29"	21.75"	29"
Length:	37.88"	42"	37.88"	42"
Weight:	140 lbs	160 lbs	160 lbs	180 lbs

* requires buck/boost transformer to run on 208V or 277V

*Optional Accessories can be found on website or manual