



# DOSATRON®

WATER POWERED DOSING TECHNOLOGY

## 11 GPM: D25RE09VFBPHY

### Product Specifications

**Call 800-523-8499 to order the Dosatron for your specific application**

Ratio Range:	1:1000 to 1:112 (.1 to .9%)
Ratio Range mL:	4 to 34 mL
Ratio Range tsp:	1 to 6.5 tsp
Water Flow Range:	0.05 to 11 GPM
Operating Pressure Range:	4.3 to 85 PSI
Available Housing Materials:	Polyacetal
Dimensions:	14" x 6 1/4"
Weight:	4 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104° F
Included Accessories:	6 ft clear suction tube, strainer, weight, mounting bracket, bypass, union, tsp/gal scale and operating manual
Recommended Accessories:	200 mesh filter, check valve, pressure regulator, flow restrictor.



**NDS™**  
NUTRIENT DELIVERY SYSTEM

The Nutrient Delivery System is customizable. More dosers can be added as needed.

NOTE: Installation illustrations are to be used as a reference guide only.

**Dosatron International**  
**2090 Sunnydale Blvd. • Clearwater, FL, USA**  
**800-523-8499 • [www.dosatronusa.com](http://www.dosatronusa.com)**

Dosatron International, Inc. is an industry leader in water-powered, proportional chemical injectors. Dosatron products are manufactured according to ISO 9001:2000 and ISO 14001:2004 standards.