©OUTLANDER™ MAX XT-P 650 T

HIGHLIGHTS

• Rotax® V-twin engine

Factory

- Intelligent Throttle Control (iTC™) with riding modes
- Anti-Lock Braking System (ABS)
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Front and rear FOX† 1.5 PODIUM† QS3 shocks
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg (3,000 lbs) WARN† winch with roller fairlead

- 14-in. cast-aluminum beadlock wheels
- 26-in. ITP Terracross radial tires
- Painted plastics for premium look
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Multifunction Analog / Digital gauge
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards



Carbon Black & Sunburst Yellow

ENGINES	650	
Туре	59 hp, Rotax 649.6 cc V-twin, liquid cooled	
Fuel Delivery System	Intelligent Throttle Control (iTC TM) with Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / L, standard engine braking	
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	
Speed category	More than 60 km/h	

SUSPENSIONS		
Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel	
Front Shocks	FOX† PODIUM† 1.5 QS3	
Rear Suspension	Torsional Trailing arm Independent (TTI) 25.1 cm travel	
Rear Shocks	FOX† PODIUM† 1.5 QS3	

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper
ABS	Standard

TIRES / WHEELS		
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.4 x 35.6 cm)	
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)	
Wheels	14-in. cast-aluminum beadlock	

DIMENSIONS / CAPACITIES				
LxWxH	238.8 x 122 x 135 cm			
Wheelbase	149.9 cm			
Ground Clearance	27.9 cm			
Seat Height	87.7 cm			
Dry Weight*	375 kg			
Rack Capacity	Front: 45 kg Rear: 90 kg			
Storage Capacity	Rear: 21.4 L			
Towing Capacity	750 kg trailer with brakes 395 kg trailer without brakes			
Fuel Capacity	20.5 L			

FEATURES			
(Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Convertible Rack System (CRS)
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn, lockable fuel cap and transmission	Protection	Heavy-duty front & rear bumpers, mudguards, aluminum taper-profile handlebar with wind deflectors and square pad
WARRANTY			

2 years

