

# RG59 CU+18/2 CU Siamese Cable

Part # BC020260XXCU



## Physical Dimensions

Component		RG59 CU +Power	
Conductor	Material	BC	
	Dia. (mm)	0.81±0.01	
Dielectric	Material	Foam PE	
	Dia. (mm)	3.70±0.10	
Shielding	Material	DCCA Braid	
	Coverage	85%	
Jacket	Material	CM FLAME RETARDANT PVC	
	Dia. (mm)	6.0±0.10	
Power Pair	Conductor	Material	BC
		Dia. (mm)	7*0.38
	Jacket 1	Material	PE
		Dia. (mm)	1.80
	Jacket 2	Material	CM FLAME RETARDANT PVC
		Dia. (mm)	5.00

Impedance(Ω)		75±3
Capacitance(pF/m)		53±3
Velocity of Propagation		83%
Return Loss	5-470MHz	≥22dB
	470-1000MHz	≥20dB

Frequency(MHz)	Attenuation (dB/100m) (±5%)
10	3.2
50	7.0
100	10.0
200	14.7
400	21.0
700	28.3
900	32.7
1000	34.6

### PACKING

(1) 500 Feet/Plastic-drum\*1/Pull-Carton,  
with Pallet

(2) 1000 Feet/Wooden-drum, With Pallet

### Printing words on the Jacket

RG59 CU SIAMESE CABLE 95% BRAIDING  
+ 18/2 CU CM 75C ROHS COMPLIANT