

US

## 1 Identification

- · Product identifier
- · Trade name: Easily Removable Ink (Red)
- Article number: 10000001242
- Relevant identified uses of the substance or mixture and uses advised against Currently no such applications are identified
- · Application of the substance / the mixture Easily Removable Ink
- $\cdot$  Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Viscot Medical, LLC.
   32 West Street
   East Hanover, NJ 07936
   Phone: 973-887-9273
   Fax: 973-887-3961
   www. viscot.com
- Information department: Tel.: 973-887-9273
- Emergency telephone numbe
  - 973-887-9273

# 2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS07

Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: 1-methoxy-2-propanol · Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. · Precautionary statements Use explosion-proof electrical/ventilating/lighting/equipment. Avoid breathing dust/fume/gas/mist/vapors/spray Wear protective gloves / eye protection / face protection. Ground/bond container and receiving equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store locked up. (Contd. on page 2)



50-1008

10-25%

Trade name: Easily Removable Ink (Red)

(Contd. of page 1) Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1FIRE 3 Fire = 3Reactivity = 0**REACTIVITY** 0 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. 3 Composition/information on ingredients

Chemical characterization: Mixtures

- Mixture of the following substances, containing non-hazardous substances and colouring agents.
- · Description: Mixture of the substances listed below with nonhazardous additions.

<ul> <li>Dangerous components</li> </ul>	:
--	---

64-17-5 ethanol

- 107-98-2 1-methoxy-2-propanol
- · Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First-aid measures

· Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

# 5 Fire-fighting measures

· Extinguishing media

• Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture No further relevant information available.

· Advice for firefighters

· Protective equipment: No special measures required.

# 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Wear protective clothing.
 Environmental precautions:
 Prevent seepage into sewage system, workpits and cellars.
 Dilute with plenty of water.
 Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up:
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Ensure adequate ventilation.
 Reference to other sections
 See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.



See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
   Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- · Specific end use (s) No further relevant information available.

Specific che de (5, no futener felevant information available.

# 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

Control parameters Components with limit values that require monitoring at the workplace: 64-17-5 ethanol (50-100%) PEL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm REL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm TLV Short-term value: 1880 mg/m<sup>3</sup>, 1000 ppm 107-98-2 1-methoxy-2-propanol (10-25%) REL Short-term value: 540 mg/m<sup>3</sup>, 150 ppm Long-term value: 360 mg/m<sup>3</sup>, 100 ppm TLVShort-term value: 369 mg/m³, 100 ppm Long-term value: 184 mg/m<sup>3</sup>, 50 ppm · Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. · Eve protection:



Tightly sealed goggles

(Contd. on page 4)

(Contd. of page 2)

(Contd. of page 3)

Not       Not         mportant information on protection of health and on safety.       -         I-value:       Not         mange in condition       Image:         Melting point/Melting range:       Und         Boiling point/Boiling range:       78         Cash point:       13         Cammability (solid, gaseous):       Not         mition temperature:       287         ecomposition temperature:       Not         into igniting:       Pro         mager of explosion:       Pro         prolosion limits:       1.7         Upper:       1.5	<pre>cohol-like determined. determined. c (172 °F) c (172 °F) applicable. c (55 °F) determined. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible. Vol %</pre>
Form:Flu Red Red AlcColor:Red AlcNor threshold:Notmortant information on protection of health and wrironment, and on safetyI-value:Notmange in conditionNotMelting point/Melting range:Und Boiling point/Boiling range:Boiling point/Boiling range:13Cash point:13Cash point:13Composition temperature:Notto igniting:Pro exppolosion limits:1.7Upper:1.5	<pre>cohol-like determined. determined. c (172 °F) c (172 °F) applicable. c (55 °F) determined. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible. Vol %</pre>
Color:Red AlcNorAlcNotNotmortant information on protection of health and wironment, and on safetyI-value:NotMelting point/Melting range:UndBoiling point/Melting range:78Cash point:13Composition temperature:287composition temperature:Notto igniting:Procomposition temperature:Notto igniting:Procomposition limits:1.7Upper:1.5	<pre>cohol-like determined. determined. c (172 °F) c (172 °F) applicable. c (55 °F) determined. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible. Vol %</pre>
Not       Not         Not       Not         mportant information on protection of health and       -         norige in condition       -         Melting point/Melting range:       Not         Boiling point/Boiling range:       13         Cash point:       13         Cammability (solid, gaseous):       Not         mition temperature:       287         ecomposition temperature:       Not         not igniting:       Pro         proposition temperature:       Not         the igniting:       Pro         proposition limits:       1.7         Upper:       15.	<pre>determined. determined. determined. °C (172 °F) °C (55 °F) applicable. ° °C (549 °F) determined. duct is not selfigniting. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible. ' Vol %</pre>
<pre>mportant information on protection of health and nvironment, and on safety </pre>	<pre>determined. °C (172 °F) °C (55 °F) applicable. ° °C (549 °F) determined. duct is not selfigniting. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible. Vol %</pre>
vironment, and on safetyI-value:NotMelting point/Melting range:UndBoiling point/Boiling range:78Cash point:13Cash point:13Cammability (solid, gaseous):Notmition temperature:287Decomposition temperature:Notto igniting:Proenger of explosion:Proexplosion limits:1.7Upper:15.	<pre>letermined. °C (172 °F) °C (55 °F) applicable. °C (549 °F) determined. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible. ' Vol %</pre>
I-value:Notnange in conditionUndMelting point/Melting range:UndBoiling point/Boiling range:78Lash point:13Lash point:15Lower:1.7Upper:15	<pre>letermined. °C (172 °F) °C (55 °F) applicable. °C (549 °F) determined. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible. ' Vol %</pre>
Melting point/Melting range:UndBoiling point/Boiling range:78Sash point:13Sammability (solid, gaseous):Notmition temperature:287Scomposition temperature:NotStore of explosion:ProSplosion limits:1.7Upper:15.	°C (172 °F) °C (55 °F) applicable. °C (549 °F) determined. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible.
Melting point/Melting range:UndBoiling point/Boiling range:78Sash point:13Sammability (solid, gaseous):Notmition temperature:287Scomposition temperature:NotStore of explosion:ProSplosion limits:1.7Upper:15.	°C (172 °F) °C (55 °F) applicable. °C (549 °F) determined. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible.
Boiling point/Boiling range:78Bash point:13Cammability (solid, gaseous):Notmition temperature:287composition temperature:Notato igniting:ProIndication fermion fermion:Propolosion limits:IndicationLower:1.7Upper:15.	°C (55 °F) applicable. °C (549 °F) determined. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible.
Cammability (solid, gaseous):Notmition temperature:287ecomposition temperature:Notato igniting:Proinger of explosion:Proexplosion limits:Lower:Lower:1.7Upper:15.	applicable. °C (549 °F) determined. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible. Vol %
mition temperature: 287 acomposition temperature: Not ato igniting: Pro anger of explosion: Pro exp plosion limits: Lower: 1.7 Upper: 15.	°C (549 °F) determined. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible.
acomposition temperature:       Not         ato igniting:       Pro         anger of explosion:       Pro         explosion limits:       1.7         Upper:       15.	determined. duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible.
atto igniting:       Pro         anger of explosion:       Pro         explosion limits:       1.7         Upper:       15.	duct is not selfigniting. duct is not explosive. However, formation of losive air/vapor mixtures are possible.
anger of explosion: properties of explosion limits: Lower: Upper: Pro exp 1.7 1.7 1.7 1.5.	duct is not explosive. However, formation of losive air/vapor mixtures are possible.
explosion limits: Lower: 1.7 Upper: 15.	losive air/vapor mixtures are possible. Vol %
Lower: 1.7 Upper: 15.	
<b>Upper:</b> 15.	
por pressure at 20 °C (68 °F): 59	0 Vol %
	hPa (44 mm Hg)
ensity at 20 °C (68 °F): 0.8	6 g/cm³ (7.177 lbs/gal)
-	determined.
	determined.
raporation rate Not	determined.
olubility in / Miscibility with	
Water: Par	tly miscible.
wrtition coefficient (n-octanol/water): Not	determined.
scosity:	
_ · · · · · · · · · · · · · · · · · · ·	mPas
Kinematic: Not	determined.
olvent content:	
Organic solvents: 78.	8 %
Solids content: 8.2	-
	physical and chemical properties given in
	tion 9.1 are rough data only, which are
	tially derived from the component's data of mixture. These data are no binding product

# 10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- $\cdot$  <code>Hazardous decomposition products:</code> No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 5) US acc. to OSHA HCS



### Trade name: Easily Removable Ink (Red)

(Contd. of page 4) The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

- · IARC (International Agency for Research on Cancer)
- None of the ingredients is listed.

• NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

#### • Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $\cdot$   $Bioaccumulative \ensuremath{\textit{potential}}$  No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

#### · Waste treatment methods

• Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

#### 14 Transport information





	(Contd. of page
· Label	3
· IMDG, IATA	
3	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
• Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E , $S-E$
· Stowage Category	B
· Transport in bulk according to Annex I.	I of
MARPOL73/78 and the IBC Code	Not applicable.
• Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
2	On cargo aircraft only: 60 L
· ADR	
• Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	5L
• Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
• UN "Model Regulation":	UN 1263 PAINT, 3, II

# 15 Regulatory information

\*

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara
· Section 355 (extremely hazardous substances):
None of the ingredient is listed.
· Section 313 (Specific toxic chemical listings):
None of the ingredients is listed.
· TSCA (Toxic Substances Control Act):
All ingredients are listed.
· Proposition 65
· Chemicals known to cause cancer:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.
· Chemicals known to cause developmental toxicity:
64-17-5 ethanol
· DSL/NDSL (Canada) All ingredients are listed
· Cancerogenity categories
· EPA (Environmental Protection Agency)
None of the ingredients is listed.
· TLV (Threshold Limit Value established by ACGIH)
64-17-5 ethanol A3
· MAK (German Maximum Workplace Concentration)
64-17-5 ethanol 5
· NIOSH-Ca (National Institute for Occupational Safety and Health)
None of the ingredients is listed.
(Contd. on page



US



· Date of preparation / last revision 01/28/2016 / 7

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the ADF: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage

of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) PBT: Persistent, Bioaccumulative and Toxic VPVB: very Persistent and very Bioaccumulative

- vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit REL: Recommended Exposure Limit
- Flam. Liq. 2: Flammable liquids, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A STOT SE 3: Specific target organ toxicity Single exposure, Hazard Category 3
- \* Data compared to the previous version altered.