


# NEW RAGE CYCLES

## INSTALLATION INSTRUCTIONS

### DUCATI SCRAMBLER/SIXTY2

#### FENDER ELIMINATOR (WRAP AROUND)

- 1 Disconnect white connector for license plate light located in front of swing arm, and re-route underneath bike (picture 1)
- 2 Remove wire from two cable clamps under swing arm
- 3 Remove 3 hugger bracket mounting screws and take hugger off (picture 2)
- 4 Remove splash shield and stock fender (picture 3,4)
- 5 Unplug connectors and remove entire fender
- 6 Remove lens off stock signals, unplug spade connectors, and pull harness out (picture 5)
- 7 Unbolt stock signals and remove from bike
- 8 Unbolt slash guard and remove from bike (picture 6)
- 9 Remove storage box from underneath seat (picture 7/8)



# NEW RAGE CYCLES

## INSTALLATION INSTRUCTIONS

### FENDER ELIMINATOR (WRAP AROUND)

- 10 Take wiring harness and plug spade connectors together, and shrink tube connections (picture 9)
  - White wires to Red wires
  - Black wires to Black wires
- 11 With supplied button head bolts and two white spacers, mount NRC turn signal bracket to fender (picture 10)
- 12 To install belly pan, use two stock bolts for lower holes, and 2 supplied M8 bolts for underneath tail light. Leave M8 bolts loose and mount fender to lower holes (picture 11/12)
- 13 Plug in plate light connector
- 14 To install fender, use stock bolts through lower mounting holes, through belly pan, into the bike, and reinstall two bolts on the side of the fender (picture 13)
- 15 Route all of your wires under seat and plug into stock harness, making sure both signals and plate light are working
- 16 Mount your license plate to the belly pan, and then re-install storage bin
- 17 Put your seat back on and ride safe

