



GROOVY 3D CORK WALL TILES

TECHNICAL SPECIFICATION

GENERAL DEFINITION AND PRODUCT COMPOSITION

Definition	Solid agglomerated cork tiles to be used as wallcoverings within buildings, contributing significantly to the acoustic and thermal performance of buildings, improving environmental comfort and reducing energy costs. Tiles are shaped by CNC machining and finished with a waterbased protector for increased water and stain resistance.
Dimensions	600 x 300 x 6 mm
Product structure and materials	CNC machined agglomerated cork (natural or toasted); CORKGUARD® Aqueous dispersion (clear or coloured).
Installation system	Glued

TECHNICAL DATA

Length and width	EN ISO 24342	600 x 300 mm ± 0.5 %
Overall thickness	ISO 7322	6 mm ± 0.2 mm
Apparent density	ISO 7322	290 Kg/m ³
Mass per unit area	EN ISO 23997	1740 g/m ² ± 10 %
Tensile strength	ISO 7322	> 1000 kPa
Compression Recuperation	ISO 7322	< 40 % > 80 %
Dimensional variation	EN ISO 23999	< 0.4 %
Moisture content	EN 12105	< 8 %
Curling	EN ISO 23999	< 6 mm
Reaction to fire	EN 13501-1	Fire class E
Formaldehyde emission	EN 12149	Fulfilled Below Detection Limit. No formaldehyde-containing products are added during the manufacturing.



GROOVY 3D CORK WALL TILES

TECHNICAL SPECIFICATION

TECHNICAL DATA

Heavy metals and specific elements Arsenic; Barium; Cadmium; Chromium; Mercury; Lead; Antimony; Selenium	EN 12149	Fulfilled None of these substances are added or have come in direct contact with the product during the manufacturing process.
Release of vinyl chloride monomer	EN 12149	Fulfilled Below Detection Limit
Thermal resistance Thermal conductivity	EN 12667	0.10 (m ² .K)/W 0.05 W/(m.K)

GENERAL DATA

Features	<p>Safe and easy to handle and install; Effective reduction of airborne sound; Increases the thermal comfort; Persistence of characteristics along time; Without the release of toxic gases when burning; Lightweight, elastic and odourless; No harmful chemicals; Contains 92% of post-industrial recycled content; Natural, biodegradable and recyclable product; Product certified FSC Controlled Wood SA-CW-002408.</p>
Packaging	<p>GROOVY tiles are packed in cardboard cartons, each containing 44 tiles, providing suitable protection for normal transport and storage conditions.</p> <p>Tiles per carton: 44 Sqm per carton: 7.92 m² Weight per carton: 14 Kg Cartons per pallet: 42 Sqm per pallet: 332.6 m²</p>
Lifetime limited warranty	<p>We certify that the product is free from manufacturing and structural defects and will remain free of these defects.</p>
Environment	<p>The use of a natural and renewable raw-material and the possibility of total recycling of the product, make GROOVY a reference in terms of ecology and environmental sustainability. GROOVY tiles are made using more than 90% cork, which is a renewable raw material. It contains no PVC and no softeners or other substances hazardous to health or the environment.</p>



Our supplier reserves the right to make changes to material and structure to improve the quality or technical performance.