G-RIB PANEL

FRONTIER METAL



G-Rib is available with our 40-Year

Warranty and has a minimum thickness
of .0153 before paint and an AZ50

Galvalume® substrate. It also carries 20
Year Perforation Warranty on a
Galvalume® steel substrate. All colors
have an Energy Star® rating and comes
with a UL® 2218 Class 4 impact rating
and a UL® 790 fire rating. G-Rib is
offered in a 80,000 PSI maximum
hardness to allow for the intricate
bends of this panel.



G-RIB TRIMS

29 GAUGE G-RIB TRIMS	PART	LENGTH
Painted Side 4 1/4" 13/16" 13/16" 13/16"	Corner	10' 4" 12' 4" 14' 4" 16' 4" 18' 4" 20' 4"
2 ½" Painted Side 13/16" 13/16" ½" Hem ½" Hem	Residential Rake	10′ 4″
Painted Side 3 ½" 2 9/16" ½" ½" 2 9/16" ½" Hem ½" Hem	Ridge Cap	10′ 4″
Painted Side 2 ½" 1" Hem %"	J Channel	10′ 4″
1 11/16" Painted Side 1" 1" 1"	Z Bar	10′ 4″
1 ½" Painted Side 15/16" 7/16" ½"	Rat Guard	10′ 4″
Painted Side	Drip Flashing	10′ 4″
3 ½" Painted Side 1 ½"	Drip Edge	10′ 4″
1 ½" Painted Side %" Hem (3 ½") x (5 ½") (7 ½")	Angle Trim	10′ 4″
4 ¼" 4 ¼" 13/16" Painted Side 13/16" ½" Hem	Eave Trim	10′ 4″

29 GAUGE G-RIB TRIMS	PART	LENGTH
4" Painted Side 6" ½" Hem	End Wall Flashing	10' 4"
Painted Side 4 ½" 13/16 13/16 ½" Hem	Side Wall Flashing	10' 4"
13/16" ½" Hem Painted Side 4 ½" ½" Hem 13/16" ½" Hem	Inside Corner	10' 4"
2 1/3/16" Painted Side 2 1/16"	Overhang Trim	10' 4"
1 ½" 2 ¾" Painted Side 3¼" ¾" ½" Hem ½" Hem	Snow Guard	10' 4"
Painted Side 13 %" 13 %"	Valley Flashing	10' 4"
8" Painted Side 8" 1/2" Hem	Transition Flashing	10' 4"
1 ¾" Painted Side	Track Cover	10' 4"
2 ¾" Painted Side > 8 ¼"	Overhead Door Trim	10' 4"