

SPECIFICATION SHEET



TRUE

FITTM

WOMEN'S

LYNX IGS V2125

Safety Specification EN ISO 20345:2022 S7L FO HRO LG SR



LADDER GRIPS

ENERGY

ABSORPTION







PUNCTURE RESISTANT (NON-METAL)

FUEL OIL-RESISTANT





HEAT-RESISTANT



KENNEDY GRATING SLIP-TESTED



Description

- A True Women's FitTM waterproof safety hiker with a sand Nubuck upper
- Feet stay dry and cool with breathable V-Dri™ waterproof lining
- Toes stay protected with a composite toecap

SCAFFOLD BOARD SLIP-TESTED

- Underfoot is safe with a flexible protective midsole
- This safety hiker is a Carbon Neutral product

Toecap

Feet are kept safe from heavy or dropped items with a strong but lightweight composite toecap, tested to 200 Joules.

Protective midsole

Feet are kept safe from sharp items entering underfoot with a strong but lightweight composite anti-penetration midsole, tested to 1,100N.

Size Available in sizes: UK 2 - 8 (35 - 42)

CERTIFIED

PRODUCT

ZER©ARBON

Weight 660g

based on a size 6 (39)

Sole

Slip safety ensured with the innovative IGSTM sole unit, featuring a water-dispersing tread and ladder grips for working safely at height, keeping the wearer stable on slippery and contaminated surfaces.

Upper

Cool feet with a honey Nubuck upper, a bellows tongue prevents water from entering, and a padded cut-away collar gives added comfort when driving and using ladders.

Footbed

Feet remain cool and sweat-free with a heel pump and heat-reducing airflow channels, while cushioned and resilient rebound PU open-cell foam offers superb comfort and support.

Lining

Feet stay dry and cool with the innovative V-Dri™ waterproof lining, featuring inside-boot climate-control technology.

Warranty

We're so confident that our boots will stand the test of time, we offer a 200-day guarantee as standard.

EN ISO 20345:2022 standards for general purpose safety footwear, plus additional (optional) safety features.

Features	Test Performed	Safety Classifications													
		SB	S1	S2	S3	S3L	\$3S	S4	S5	S5L	S5S	S6	S7	S7L	S7S
	Slip resistance now seen as mandatory, so no symbol given	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
SB	Safety toecap protection only, tested with 200 J impact and 15 $\rm kN$ compression force	\checkmark	\checkmark	\checkmark	~	\checkmark	✓	~	\checkmark						
А	Anti-static: electrical resistance between foot and ground of between 0.1 and 1,000 mega ohms*		\checkmark												
E	Energy absorption of the seat region: energy absorbed to be not less than 20 J		\checkmark												
WPA	Water penetration and absorption (water-resistant and breathable)			\checkmark	\checkmark	\checkmark	\checkmark					\checkmark	\checkmark	✓	\checkmark
WR	Water-resistant footwear (waterproof membrane)											\checkmark	~	\checkmark	\checkmark
Р	(Metal insert type P) Penetration-resistant outsole: Lowest penetration value required shall not be less than 1,100 N				\checkmark				\checkmark				\checkmark		
PL	(Non-metal insert type PL) Penetration-resistant outsole: Lowest penetration value required shall not be less than 1,100 N and no separation of the layers shall occur during all tests					~				~				~	
PS	(Non-metal insert type PS) Penetration-resistant outsole: Average penetration value shall not be less than 1,100 N with no single value shall be lower than 950 N						\checkmark				\checkmark				\checkmark

Additional Safety Features

HRO	Heat-resistant outsole compound: shall withstand 300°C for 60 seconds
FO	Resistance to fuel oil
LG	Ladder grip
SC	Scuff cap abrasion
CR	Cut-resistant upper: cut-resistant index to exceed 2.5
Μ	Metatarsal protection 100 J impact energy
SR	Slip test will feature glycerine on ceramic tile surface
С	Partially conductive footwear. The electrical resistance shall not be greater than 0.1 mega ohms between foot and ground*
Cl	Insulation against the cold: 30 minutes at -17°C, the decrease shall not be more than 10°C
HI	Insulation against heat: 30 minutes at 150°C, the rise shall not be higher than 22°C
AN	Ankle protection: 10 N impact mean transferred force shall not exceed 10 kN and no single value shall exceed 15 kN

FOOT HEALTH

For foot health advice, scan the QR code.



BOOT CARE

For boot care advice, scan the QR code.





If you're unsure if these are the right boots for you and your environment, head to our boot finder by scanning the QR code and we'll give you our expert recommendations from the V12 range.

sales@V12footwear.com +44 (0)1249 651 900 V12footwear.com