

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Egg Nog at 10% in DPG

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial

Use of the substance/mixture : Perfumes, fragrances
Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Forget Me Not Oils

Calle Torrevieja 2, San Miguel de salinas

www.forgetmenotoilseurope.com & forgetmenothf@gmail.com

1.4. Emergency telephone number

0034 711024907

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : -

Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P273 - Avoid release to the environment.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

EUH-statements : EUH208 - Contains Eugenol, Cinnamic aldehyde, beta-Caryophyllene. May produce an

allergic reaction.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

EN (English) 1/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	4.8 – 6.8	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802- 33	0.42 – 0.88	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Cinnamic aldehyde	CAS-No.: 104-55-2 EC-No.: 203-213-9 REACH-no: 01-2119935242- 45	0.204 – 0.416	Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Hexamethylindanopyran	CAS-No.: 1222-05-5 EC-No.: 214-946-9 EC Index-No.: 603-212-00-7 REACH-no: 01-2119488227-	0.12 – 0.235	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
beta-Caryophyllene	CAS-No.: 87-44-5 EC-No.: 201-746-1 REACH-no: 01-2120745237- 53	0.044 – 0.128	Skin Sens. 1B, H317 Asp. Tox. 1, H304
Ethyl acetate substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-	0.01 – 0.025	Flam. Liq. 1, H224 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

EN (English) 2/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent

formation of vapour.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep

container closed when not in use.

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

EN (English) 3/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

3.1.1 National occupational exposure and biological limit values	
Ethyl acetate (141-78-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	734 mg/m³
IOEL TWA [ppm]	200 ppm
IOEL STEL	1468 mg/m³
IOEL STEL [ppm]	400 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	734 mg/m³
MAK (OEL TWA) [ppm]	200 ppm
MAK (OEL STEL)	1468 mg/m³
MAK (OEL STEL) [ppm]	400 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	734 mg/m³
GVI (OEL TWA) [2]	200 ppm
KGVI (OEL STEL)	1468 mg/m³
KGVI (OEL STEL) [ppm]	400 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	700 mg/m³
Denmark - Occupational Exposure Limits	
OEL TWA [1]	540 mg/m³
OEL TWA [2]	150 ppm

EN (English) 4/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acetate (141-78-6)			
Estonia - Occupational Exposure Limits			
OEL TWA	500 mg/m³		
OEL TWA [ppm]	150 ppm		
OEL STEL	1100 mg/m³		
OEL STEL [ppm]	300 ppm		
Finland - Occupational Exposure Limits			
HTP (OEL TWA) [1]	730 mg/m³		
HTP (OEL TWA) [2]	200 ppm		
HTP (OEL STEL)	1470 mg/m³		
HTP (OEL STEL) [ppm]	400 ppm		
France - Occupational Exposure Limits			
VME (OEL TWA)	1400 mg/m³		
VME (OEL TWA) [ppm]	400 ppm		
Germany - Occupational Exposure Limits (TRGS 90	0)		
AGW (OEL TWA) [1]	730 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
AGW (OEL TWA) [2]	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
Gibraltar - Occupational Exposure Limits			
OEL TWA	200 mg/m³		
OEL TWA [ppm]	734 ppm		
OEL STEL	400 mg/m³		
OEL STEL [ppm]	1468 ppm		
Greece - Occupational Exposure Limits			
OEL TWA	734 mg/m³		
OEL TWA [ppm]	200 ppm		
OEL STEL	1468 mg/m³		
OEL STEL [ppm]	400 ppm		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	734 mg/m³		
CK (OEL STEL)	1468 mg/m³		
OEL chemical category	Sensitizer		
Ireland - Occupational Exposure Limits			
OEL TWA [1]	734 mg/m³		
OEL TWA [2]	200 ppm		
OEL STEL	1468 mg/m³		
OEL STEL [ppm]	400 ppm		
Italy - Occupational Exposure Limits			
OEL TWA	734 mg/m³		
OEL TWA [ppm]	200 ppm		

EN (English) 5/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acetate (141-78-6)		
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	200 mg/m³	
OEL TWA [ppm]	54 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	500 mg/m³	
IPRV (OEL TWA) [ppm]	150 ppm	
NRV (OEL C)	1100 mg/m³	
NRV (OEL C) [ppm]	300 ppm	
Luxembourg - Occupational Exposure Limits		
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	734 mg/m³	
TGG-15min (OEL STEL)	1468 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	734 mg/m³	
NDSCh (OEL STEL)	1468 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	734 mg/m³ (indicative limit value)	
OEL TWA [ppm]	200 ppm (indicative limit value)	
OEL STEL	1468 mg/m³ (indicative limit value)	
OEL STEL [ppm]	400 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	400 mg/m³	
OEL TWA [ppm]	111 ppm	
OEL STEL	500 mg/m³	
OEL STEL [ppm]	139 ppm	
Slovakia - Occupational Exposure Limits	Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	734 mg/m³	
NPHV (OEL TWA) [2]	200 ppm	
NPHV (OEL C)	1100 mg/m³	

EN (English) 6/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Stovenia - Occupational Exposure Limits 734 mg/m³ OEL TWA 734 mg/m³ OEL STEL 1468 mg/m³ OEL STEL (ppm] 400 ppm Spain - Occupational Exposure Limits VLA-ED (OEL TWA) [1] 734 mg/m³ VLA-ED (OEL TWA) [2] 200 ppm VLA-ED (OEL STEL) 1468 mg/m³ VLA-ED (OEL STEL) [ppm] 400 ppm Sweder - Occupational Exposure Limits NSV (OEL STEL) [ppm] 550 mg/m³ NGY (OEL TWA) [ppm] 150 ppm KTV (OEL STEL) [ppm] 300 ppm KTV (OEL STEL) [ppm] 300 ppm KTV (OEL STEL) [ppm] 300 ppm WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) [ppm] 400 ppm WEL STEL (OEL STEL) [ppm] 400 ppm WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits VLA-ED (OEL TWA) [2] Grenseverdi (OEL TWA) [2] 200 ppm Kortidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Kortidsverdi (OEL STEL) [ppm] 400 mg/m³<	Ethyl acetate (141-78-6)		
OEL TWAE [ppm] 200 ppm OEL STEL [ppm] 4468 mg/m³ OEL STEL [ppm] 400 ppm Spain - Occupational Exposure Limits VLA-ED (OEL TWA) [1] 734 mg/m³ VLA-ED (OEL TWA) [2] 200 ppm VLA-EC (OEL STEL) [ppm] 408 mg/m³ VLA-EC (OEL STEL) [ppm] 409 ppm Sweden - Occupational Exposure Limits NGV (OEL TWA) [ppm] 150 ppm KTV (OEL STEL) [ppm] 300 ppm KTV (OEL STEL) [ppm] 300 ppm WEL TWA (Ppm] [1] 734 mg/m³ KTV (OEL STEL) [ppm] 300 ppm WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [1] 734 mg/m³ WEL STEL (OEL STEL) 400 ppm WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits WEL STEL (OEL STEL) [ppm] 734 mg/m³ Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Kortidsverdi (OEL STEL) [ppm] 468 mg/m³ (value from the regulation) Kortidsverdi (OEL STEL) [ppm] 400 ppm (valu	Slovenia - Occupational Exposure Limits		
OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Spain - Occupational Exposure Limits VLA-ED (OEL TWA) [1] 734 mg/m³ VLA-ED (OEL TWA) [2] 200 ppm VLA-EC (OEL STEL) 1468 mg/m³ VLA-EC (OEL STEL) [ppm] 400 ppm Sweden - Occupational Exposure Limits NGV (OEL TWA) [ppm] 550 mg/m³ NGV (OEL TWA) [ppm] 150 ppm KTV (OEL STEL) [ppm] 300 ppm WRIT (OEL STEL) [ppm] WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits WRIT (OEL STEL) [ppm] 734 mg/m³ MRIT (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits WRIT (OEL STEL) [ppm] 734 mg/m³ Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL STEL) [ppm] 468 mg/m³ (value from the regulation) Kortidseverdi (OEL STEL) [pm] 468 mg/m³ (value from the regulati	OEL TWA	734 mg/m³	
OEL STEL [ppm] 400 ppm Spain - Occupational Exposure Limits VLA-ED (OEL TWA) [1] 734 mg/m² VLA-ED (OEL TWA) [2] 200 ppm VLA-EC (OEL STEL) 1468 mg/m² VLA-EC (OEL STEL) [ppm] 400 ppm Sweden - Occupational Exposure Limits NGY (OEL TWA) [ppm] 550 mg/m³ NGY (OEL TWA) [ppm] 150 ppm KTV (OEL STEL) [ppm] 300 ppm WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) [ppm] 468 mg/m³ WEL STEL (OEL STEL) [ppm] 468 mg/m³ WEL STEL (OEL STEL) [ppm] 734 mg/m³ Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Kortidsverdi (OEL STEL) [ppm] 406 mg/m³ (value from the regulation) Kortidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits 400 ppm (value from the regulation) <td< td=""><td>OEL TWA [ppm]</td><td>200 ppm</td></td<>	OEL TWA [ppm]	200 ppm	
Spain - Occupational Exposure Limits VLA-ED (OEL TWA) [1] 734 mg/m³ VLA-ED (OEL TWA) [2] 200 ppm VLA-EC (OEL STEL) 1468 mg/m³ VLA-EC (OEL STEL) [ppm] 400 ppm Sweden - Occupational Exposure Limits TWA NGY (OEL TWA) [ppm] 150 ppm KTY (OEL STEL) [ppm] 300 ppm KTY (OEL STEL) [ppm] 300 ppm WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) [ppm] 468 mg/m³ WEL STEL (OEL STEL) [ppm] 460 ppm WEL STEL (OEL STEL) [ppm] 734 mg/m³ Grenseverdi (OEL TWA) [2] 460 ppm Morway - Occupational Exposure Limits 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Grenseverdi (OEL TWA) [2] 200 ppm Kortidsverdi (OEL STEL) [ppm] 734 mg/m³ Kortidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Kortidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzertand - Occupational Exposure Limits 400 ppm (value from the regulation)	OEL STEL	1468 mg/m³	
VLA-ED (OEL TWA) [1] 734 mg/m³ VLA-ED (OEL TWA) [2] 200 ppm VLA-EC (OEL STEL) 1468 mg/m³ VLA-EC (OEL STEL) [ppm] 400 ppm Sweden - Occupational Exposure Limits NGV (OEL TWA) 550 mg/m³ NGV (OEL TWA) [ppm] 150 ppm KTV (OEL STEL) [ppm] 300 ppm WRIT (OEL STEL) [ppm] WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits Verage of (OEL TWA) [1] Grenseverdi (OEL TWA) [2] 200 ppm Kortidsverdi (OEL TWA) [2] 200 ppm Kortidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Kortidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits Verage of (OEL TWA) [1] MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) [ppm] 400 ppm	OEL STEL [ppm]	400 ppm	
VLA-ED (OEL TWA) [2] 200 ppm VLA-EC (OEL STEL) 1468 mg/m³ VLA-EC (OEL STEL) [ppm] 400 ppm Sweden - Occupational Exposure Limits NGV (OEL TWA) 550 mg/m³ NGV (OEL TWA) [ppm] 150 ppm KTV (OEL STEL) 1100 mg/m³ KTV (OEL STEL) [ppm] 300 ppm United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits 500 ppm Genseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Kortidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Kortidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits 500 ppm MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) [ppm] 400 ppm	Spain - Occupational Exposure Limits		
VLA-EC (OEL STEL) 1468 mg/m³ VLA-EC (OEL STEL) [ppm] 400 ppm Sweden - Occupational Exposure Limits NGV (OEL TWA) 550 mg/m³ NGV (OEL TWA) [ppm] 150 ppm KTV (OEL STEL) 1100 mg/m³ KTV (OEL STEL) [ppm] 300 ppm United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits WL MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL STEL) 200 ppm KZGW (OEL STEL) 400 ppm	VLA-ED (OEL TWA) [1]	734 mg/m³	
VLA-EC (OEL STEL) [ppm] 400 ppm Sweden - Occupational Exposure Limits 550 mg/m³ NGV (OEL TWA) [ppm] 150 ppm KTV (OEL STEL) [ppm] 300 ppm KTV (OEL STEL) [ppm] 300 ppm United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits T34 mg/m³ Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits TMK (OEL TWA) [1] MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) [ppm] 400 ppm	VLA-ED (OEL TWA) [2]	200 ppm	
Sweden - Occupational Exposure Limits NGV (OEL TWA) 550 mg/m³ NGV (OEL TWA) [ppm] 150 ppm KTV (OEL STEL) 1100 mg/m³ KTV (OEL STEL) [ppm] 300 ppm United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits To mg/m³ MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	VLA-EC (OEL STEL)	1468 mg/m³	
NGV (OEL TWA) 550 mg/m³ NGV (OEL TWA) [ppm] 150 ppm KTV (OEL STEL) 1100 mg/m³ KTV (OEL STEL) [ppm] 300 ppm United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Kortidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Kortidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) [ppm] 400 ppm/m³ KZGW (OEL STEL) [ppm] 400 ppm	VLA-EC (OEL STEL) [ppm]	400 ppm	
NGV (OEL TWA) [ppm] 150 ppm KTV (OEL STEL) 1100 mg/m³ KTV (OEL STEL) [ppm] 300 ppm United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Kortidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Kortidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] MAK (OEL TWA) [2] 200 ppm MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) 400 ppm	Sweden - Occupational Exposure Limits		
KTV (OEL STEL) 1100 mg/m³ KTV (OEL STEL) [ppm] 300 ppm United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Kortidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Kortidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	NGV (OEL TWA)	550 mg/m³	
KTV (OEL STEL) [ppm] 300 ppm United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL STEL) 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits 734 mg/m³ Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) 1460 mg/m³	NGV (OEL TWA) [ppm]	150 ppm	
United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits *** MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	KTV (OEL STEL)	1100 mg/m³	
WEL TWA (OEL TWA) [1] 734 mg/m³ WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] MAK (OEL TWA) [2] 200 ppm MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	KTV (OEL STEL) [ppm]	300 ppm	
WEL TWA (OEL TWA) [2] 200 ppm WEL STEL (OEL STEL) 1468 mg/m³ WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) [ppm] 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	United Kingdom - Occupational Exposure Limits		
WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 400 ppm KZGW (OEL STEL) 400 ppm KZGW (OEL STEL) 400 ppm	WEL TWA (OEL TWA) [1]	734 mg/m³	
WEL STEL (OEL STEL) [ppm] 400 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	WEL TWA (OEL TWA) [2]	200 ppm	
Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	WEL STEL (OEL STEL)	1468 mg/m³	
Grenseverdi (OEL TWA) [1] 734 mg/m³ Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) [ppm] 400 ppm KZGW (OEL STEL) [ppm] 400 ppm	WEL STEL (OEL STEL) [ppm]	400 ppm	
Grenseverdi (OEL TWA) [2] 200 ppm Korttidsverdi (OEL STEL) 1468 mg/m³ (value from the regulation) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	Norway - Occupational Exposure Limits		
Korttidsverdi (OEL STEL) Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) KZGW (OEL STEL) [ppm] 400 ppm 400 ppm	Grenseverdi (OEL TWA) [1]	734 mg/m³	
Korttidsverdi (OEL STEL) [ppm] 400 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) [ppm] 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	Grenseverdi (OEL TWA) [2]	200 ppm	
Switzerland - Occupational Exposure Limits MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	Korttidsverdi (OEL STEL)	1468 mg/m³ (value from the regulation)	
MAK (OEL TWA) [1] 730 mg/m³ MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	Korttidsverdi (OEL STEL) [ppm]	400 ppm (value from the regulation)	
MAK (OEL TWA) [2] 200 ppm KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	Switzerland - Occupational Exposure Limits		
KZGW (OEL STEL) 1460 mg/m³ KZGW (OEL STEL) [ppm] 400 ppm	MAK (OEL TWA) [1]	730 mg/m³	
KZGW (OEL STEL) [ppm] 400 ppm	MAK (OEL TWA) [2]	200 ppm	
	KZGW (OEL STEL)	1460 mg/m³	
USA - ACGIH - Occupational Exposure Limits	KZGW (OEL STEL) [ppm]	400 ppm	
	USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm] 400 ppm	ACGIH OEL TWA [ppm]	400 ppm	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

EN (English) 7/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

8.2.2.2. Skin protection

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Physical state

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

: Liquid

Colour Standard. Odour characteristic. Odour threshold : No data available рΗ : No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : No data available Freezing point : No data available : No data available Boiling point : > 93 °C Flash point

Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : Non flammable. : No data available Vapour pressure Relative vapour density at 20 °C : No data available Relative density : No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Viscosity, kinematic : No data available : No data available Viscosity, dynamic Explosive properties : No data available Oxidising properties : No data available **Explosive limits** : No data available

EN (English) 8/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Benzyl benzoate (120-51-4)		
LD50 oral rat	500 mg/kg	
LD50 oral	1500 mg/kg bodyweight	
LD50 dermal rabbit	4000 mg/kg	
LD50 dermal	4000 mg/kg bodyweight	
Eugenol (97-53-0)		
LD50 oral rat	1930 mg/kg	
LD50 oral	2500 mg/kg bodyweight	
Cinnamic aldehyde (104-55-2)		
LD50 oral rat	2220 mg/kg	
LD50 oral	2200 mg/kg bodyweight	
LD50 dermal rabbit	1260 mg/kg	
LD50 dermal	1100 mg/kg bodyweight	

EN (English) 9/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg
LD50 dermal rabbit	> 18000 mg/kg
LC50 Inhalation - Rat [ppm]	4000 ppm/4h
Hexamethylindanopyran (1222-05-5)	
LD50 oral rat	> 3250 mg/kg
LD50 dermal rabbit	> 3250 mg/kg
Skin corrosion/irritation Additional information Serious eye damage/irritation Additional information Respiratory or skin sensitisation Additional information Germ cell mutagenicity Additional information Carcinogenicity Additional information	Not classified Based on available data, the classification criteria are not met Not classified Based on available data, the classification criteria are not met Not classified Based on available data, the classification criteria are not met Not classified Based on available data, the classification criteria are not met Not classified Based on available data, the classification criteria are not met Rot classified Based on available data, the classification criteria are not met
Eugenol (97-53-0)	
IARC group	3 - Not classifiable
Reproductive toxicity Additional information STOT-single exposure Additional information	Not classified Based on available data, the classification criteria are not met Not classified Based on available data, the classification criteria are not met
Ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure Additional information Aspiration hazard Additional information Potential adverse human health effects and symptoms	Not classified Based on available data, the classification criteria are not met Not classified Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.

(chronic)

Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
NOEC (chronic)	0.168 mg/l
Eugenol (97-53-0)	
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
Ethyl acetate (141-78-6)	
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

EN (English) 10/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acetate (141-78-6)	
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Hexamethylindanopyran (1222-05-5)	
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas
EC50 - Crustacea [2]	260 μg/l REACH Dossier
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier

12.2. Persistence and degradability

Egg Nog at 10% in DPG	
Persistence and degradability	Not established.
Benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

Egg Nog at 10% in DPG	
Bioaccumulative potential	Not established.
Benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.
Eugenol (97-53-0)	
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5)
Cinnamic aldehyde (104-55-2)	
Partition coefficient n-octanol/water (Log Pow)	2.1065 (at 25 °C)
Ethyl acetate (141-78-6)	
BCF - Fish [1]	(30 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	0.73 (at 20 °C (at pH 7)
Hexamethylindanopyran (1222-05-5)	
BCF - Fish [1]	(1618 dimensionless (whole body w.w.)
Partition coefficient n-octanol/water (Log Pow)	5.3 (at 25 °C (at pH 7)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment.

EN (English) 11/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1 UN number

UN-No. (ADR) : Not applicable
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : Not applicable
UN-No. (ADN) : Not applicable
UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Not applicable

EN (English) 12/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

List of sensitizing substances (TRGS 907) : Contains sensitizing substances according TRGS 907

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed SZW-lijst van reprotoxische stoffen – : None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

EN (English) 13/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Eugenol, Cinnamic aldehyde, beta-Caryophyllene. May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
H224	Extremely flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

EN (English) 14/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

EN (English) 15/15