

Rugged economical plastic distributor heads for single in-out applications.

990S/890S/890C/RA201 890 Plastic Distributor Heads



990S • D1226



890S • D7171



890C • D7173



RA201 890 • R7009

The 990S, 890S, 890C and RA201 890 Distributor Heads are molded of rugged composite plastic. These distribution heads are designed for single in-out applications on filters such as sediment removal, taste, odor, pH neutralization or demineralization.

These economical heads will fit onto standard 2½" - 8 NPSM tank openings. A tapered riser port simplifies installation of riser pipes. Inlet and outlet openings are designed for easy, straight line installation. An additional ¾" or ½" outlet is available on the 890C and RA201 890 for water sampling, conductivity lights or other applications. A complete line of top and bottom distributors and riser pipes is available. Consult factory for additional information.

Operating Pressures: 20-125 psi / 138-862 kPa

Temperature Ranges: 40-110°F / 4-43°C

Install only on cold water supplies

ORDER NO.	DESCRIPTION	TANK OPENING SIZE	INLET/OUTLET OPENINGS	SIDE PORT OPENING	RISER PIPE SIZE	O-RING SEAL
D1226	990S	2½" - 8 NPSM	1" FNPT	Not Applicable	1.050"	Face Seal
D7171	890S	2½" - 8 NPSM	¾" FNPT	Not Applicable	13/16"	Face Seal
D7173	890C	2½" - 8 NPSM	¾" FNPT	¾" FNPT	13/16"	Face Seal
R7009	RA201 890	2½" - 8 NPSM	¾" FNPT	½" FNPT	13/16"	Face Seal



www.clackcorp.com

Clack Corporation

4462 DURAFORM LANE • WINDSOR, WISCONSIN 53598-9716 USA

PHONE (608) 846-3010 FAX (608) 846-2586 SALES/CUSTOMER SERVICE FAX (800) 755-3010

Form No. 2716 • 7/29/2014