WTF SERIES | TIME CLOCK ACID NEUTRALIZERS






- Increases pH level of water to a safe limit
- Protects copper plumbing systems and helps eliminate pinhole leaks
- Eliminates blue or green stains on fixtures
- Prevents scratching and pitting of porcelain and cookware





WTF SERIES | TIME CLOCK ACID NEUTRALIZERS



WTF10ANX-V WTF15ANX-V WTF25ANX-V

FEATURES

- Fiberglass tank will not rust, durable design and efficient operation
- 12 Day Fleck 5600 Valve
- High flow bypass valve included
- Dome hole fill port

Warranty

Fiberglass Tank: 10 years Control Valve: 3 years Timer/Motor: 3 years

MEDIA OPTIONS (Sold separately)

Extra Fine Calcite



80% Calcite
20% Mag Oxide



Fine Calcite



70% Calcite 30% Mag Oxide



PH LEVELS					
7.0	Neutral				
6.8 - 6.9	Slightly Acidic				
6.0 - 6.7	Moderately Acidic				
4.0 - 5.9	Extremely Acidic				

Recommended range: 7.0 - 8.5

Low pH causes blue or green stains and corrosion of plumbing fixtures. It can also cause pitting of porcelain and enamel fixtures and dishes.

Add filter media about every 3 to 6 months

Medium Calcite



60% Calcite 40% Mag Oxide



Processed Magnesium Oxide



100% Natural Magnesium Oxide



VORTECH PLATE



Environmentally friendly, reduces backwash requirement by up to 30%.

Designed for over 6,500 lbs. load capacity.

High flow design maximizes today's high efficiency control valve technology.

FLECK 5600 VALVE



1-12 day time clock valve, simple to adjust and easy to service with quick access to all internal components.

Stainless steel bypass valve.

Regenerates at pre-set intervals.

SPECIFICATIONS

Model	Capacity Cu. Ft.	Tank Size Inches	Service/Peak Flow Rate	Backwash Flow Rate	Gal. Per Backwash	Pipe Size In/Out	pH Range	50 lb bags of Media needed
WTF10ANX-V	1.0	10" x 40"	4 gpm	5.0 gpm	200	1"	5 - 6.9	2 bags
WTF15ANX-V	1.5	10" x 54"	5/6 gpm	5.0 gpm	200	1"	5 - 6.9	3 bags
WTF25ANX-V	2.5	13" x 54"	7/9 gpm	7.0 gpm	280	1″	5 - 6.9	5 bags